

1983

MEMORIAL

Journal Officiel
du Grand-Duché de
Luxembourg



MEMORIAL

Amtsblatt
des Großherzogtums
Luxemburg

RECUEIL DE LEGISLATION

A — N° 128

21 juillet 2014

S o m m a i r e

Règlement grand-ducal du 10 mars 2014 sur le certificat de qualification des entreprises exploitant des entraîneurs synthétiques de vol pour avions et hélicoptères page 1984

Règlement grand-ducal du 10 mars 2014 sur le certificat de qualification des entreprises exploitant des entraîneurs synthétiques de vol pour avions et hélicoptères.

Nous Henri, Grand-Duc de Luxembourg, Duc de Nassau,

Vu le règlement (CE) n° 216/2008 modifié du Parlement européen et du Conseil du 20 février 2008 concernant des règles communes dans le domaine de l'aviation civile et instituant une Agence européenne de la sécurité aérienne, et abrogeant la directive 91/670/CEE du Conseil, le règlement (CE) n° 1592/2002 et la directive 2004/36/CE;

Vu le règlement (UE) n° 1178/2011 modifié de la Commission du 3 novembre 2011 déterminant les exigences techniques et les procédures administratives applicables au personnel navigant de l'aviation civile conformément au règlement (CE) n° 216/2008 du Parlement européen et du Conseil;

Vu la loi modifiée du 31 janvier 1948 relative à la réglementation de la navigation aérienne;

Vu la loi modifiée du 19 mai 1999 ayant pour objet a) de réglementer l'accès au marché de l'assistance en escale à l'aéroport de Luxembourg; b) de créer un cadre réglementaire dans le domaine de la sûreté de l'aviation civile et, c) d'instituer une Direction de l'Aviation Civile;

Vu les codes JAR-FSTD (A) – Aeroplane Flight Simulation Training Devices et JAR-FSTD (H) – Helicopter Flight Simulation Training Devices édictés en date du 1^{er} mai 2008 par les Autorités Conjointes de l'Aviation (JAA: Joint Aviation Authorities);

Vu les documents administratifs et d'orientation des JAA; Section Six: Entraîneurs synthétiques de vol (FSTD) publiés en date du 1^{er} février 2008;

Vu l'article 2 (1) de la loi du 12 juillet 1996 portant réforme du Conseil d'Etat et considérant qu'il y a urgence;

Sur le rapport de Notre Ministre du Développement durable et des Infrastructures et après délibération du Gouvernement en Conseil;

Arrêtons:

Art. 1^{er}. Champ d'application

Le présent règlement grand-ducal s'applique aux entreprises qui exploitent des entraîneurs synthétiques de vol pour avions et hélicoptères sur le territoire du Grand-Duché de Luxembourg, dénommées ci-après «les exploitants». Sans préjudice notamment d'autres conditions complémentaires, techniques, économiques ou sociales qui peuvent exister par ailleurs, le règlement prescrit les conditions techniques applicables aux exploitants, énoncées dans les codes JAR-FSTD (A) et JAR-FSTD (H).

Les codes JAR-FSTD (A) et JAR-FSTD (H) figurent à l'annexe I respectivement à l'annexe II du présent règlement et en font partie intégrante.

Art. 2. Modalités et conditions d'obtention du certificat de qualification des exploitants d'entraîneurs synthétiques de vol pour avions et hélicoptères

Pour l'exercice de leurs activités de simulation de vol, les exploitants désignés à l'article 1^{er} doivent être titulaires d'un certificat de qualification les autorisant à pratiquer la simulation de vol, délivré par la Direction de l'Aviation Civile (DAC) en conformité avec les dispositions afférentes des codes JAR-FSTD (A) et JAR-FSTD (H).

Les codes JAR-FSTD (A) et JAR-FSTD (H) régissent l'octroi et le renouvellement du certificat de qualification ainsi que l'extension de son champ d'application.

L'octroi du certificat autorisant la pratique de la simulation de vol est soumis en particulier à la condition que l'exploitant ait nommé un dirigeant responsable ainsi qu'un responsable qualité conformément au paragraphe A.025 du code JAR-FSTD (A) pour les entraîneurs synthétiques de vol pour avions respectivement au paragraphe H.025 du code JAR-FSTD (H) pour les entraîneurs synthétiques de vol pour hélicoptères.

Les responsables en question doivent être agréés par la DAC.

Les conditions d'obtention d'un certificat de qualification permettant la pratique de la simulation de vol sont régies par le paragraphe A.030. du code JAR-FSTD (A) pour les entraîneurs synthétiques de vol pour avions ainsi que par le paragraphe H.030. du code JAR-FSTD (H) pour les entraîneurs synthétiques de vol pour hélicoptères.

Art. 3. Durée de validité du certificat de qualification

La durée de validité du certificat de qualification initial autorisant à pratiquer les activités de simulation de vol est d'une année. Le certificat peut être prolongé d'année en année sur demande expresse de l'exploitant. Les modalités entourant cette durée de validité sont régies par le paragraphe A.020 du code JAR-FSTD (A) pour les entraîneurs synthétiques de vol pour avions ainsi que par le paragraphe H.020 du code JAR-FSTD (H) pour les entraîneurs synthétiques de vol pour hélicoptères.

Art. 4. Retrait du certificat de qualification

La DAC peut prononcer le retrait temporaire ou définitif du certificat de qualification autorisant à pratiquer les activités de simulation de vol ou limiter le domaine d'activité du titulaire du certificat, notamment lorsque:

- a) les conditions régissant l'octroi du certificat de qualification autorisant à pratiquer les activités de simulation de vol ne sont plus remplies;
- b) des dispositions qui s'avèrent déterminantes pour l'octroi du certificat de qualification ont été violées de manière grave ou répétée;

- c) l'accès à l'entreprise de l'exploitant est interdit à la DAC ainsi qu'aux services compétents désignés à l'article 7 ci-après, ou que l'exploitant refuse de fournir à la DAC les documents requis pour contrôler l'application des dispositions du présent règlement et des codes JAR-FSTD (A) et JAR-FSTD (H).

Art. 5. Dispositions techniques

Le ministre peut, sur proposition de la Direction de l'aviation civile et dans le but d'assurer un maniement adéquat des entraîneurs synthétiques de vol pour avions ou hélicoptères, édicter sous forme d'un règlement des instructions ou des directives qui s'adressent aux exploitants et qui ont pour objet de soumettre à certaines conditions, limiter, voire interdire certaines opérations.

Ces dispositions techniques énoncent les motifs justifiant leur diffusion et précisent leur champ d'application. Ils indiquent les mesures que doivent prendre les exploitants pour leur application et complètent les dispositions des codes JAR-FSTD (A) et JAR-FSTD (H).

Art. 6. Exceptions

Dans des cas dûment motivés, la DAC peut, à titre exceptionnel et provisoire, accorder des dérogations aux dispositions des codes JAR-FSTD (A) et JAR-FSTD (H) lorsqu'elle estime que le besoin existe, notamment pour prévenir les cas de rigueur et, sous réserve du respect de toute condition supplémentaire qu'elle considère comme nécessaire, pour assurer, dans ces cas particuliers, un niveau d'opération jugé équivalent.

Art. 7. Vérifications et surveillance

La DAC peut effectuer les vérifications et la surveillance qu'elle juge nécessaires pour l'application du présent règlement. Elle peut également, en cas de besoin, avoir recours à cet effet à des organismes spécialisés habilités à cet effet.

Art. 8. Dispositions transitoires

La DAC peut, en fonction de la complexité technique, fixer à chaque exploitant un délai dans lequel ce dernier doit adapter son exploitation et son règlement interne aux dispositions du présent règlement. Ce délai ne peut pas dépasser un an à partir de la date d'entrée en vigueur du présent règlement.

Les règlements internes en usage auprès des exploitants au moment de l'entrée en vigueur du présent règlement restent en vigueur jusqu'à leur remplacement par de nouveaux règlements internes.

Les autorisations anciennes délivrées uniquement sur base des codes JAR-FSTD (A) et JAR-FSTD (H) sont réputées avoir été délivrées en conformité avec les dispositions du présent règlement.

Art. 9. Disposition finale

Notre Ministre du Développement durable et des Infrastructures est chargé de l'exécution du présent règlement qui sera publié au Mémorial.

Le Ministre du Développement durable
et des Infrastructures,
François Bausch

Château de Berg, le 10 mars 2014.
Henri

Annexe I

Code JAR-FSTD (A) – Entraîneurs synthétiques de vol pour avions

Annexe II

Code JAR – FSTD (H) – Entraîneurs synthétiques de vol pour hélicoptères

1986

Annexe I

Code JAR-FSTD (A) – Entraîneurs synthétiques de vol pour avions

Joint Aviation Requirements

JAR–FSTD A

Aeroplane Flight Simulation Training Devices

Joint Aviation Authorities

1987



Joint Aviation Requirements

JAR-FSTD A Aeroplane Flight Simulation Training Devices

Initial issue
1 May 2008

All rights reserved

The members of the Joint Aviation Authorities Committee are representatives of the Civil Aviation Authorities of the countries that have signed the 'Arrangements Concerning the Development and the Acceptance of Joint Aviation Requirements'. A list of these countries is kept by European Civil Aviation Conference, 3 bis Villa Emile Bergerat, 92522 NEUILLY SUR SEINE Cedex, France.*

Further copies of the Joint Aviation Requirements can be purchased from Information Handling Services (IHS), whose world-wide offices are listed on the JAA website (www.jaa.nl) and IHS website (www.global.ihs.com)

For electronic versions of Joint Aviation Authorities Documents please refer to the website of Information Handling Services (IHS) on www.ihsaviation.com, where you will find information on how to order.

Enquiries regarding the contents should be addressed to the JAA, Saturnusstraat 40-44, PO Box 3000, 2130 KA HOOFDORP, The Netherlands (publications@jaat.eu).

*These countries are:

Albania, Armenia, Austria, [Azerbaijan], Belgium, Bosnia and Herzegovina, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, European Aviation Safety Agency, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Monaco, Netherlands, Norway, Poland, Portugal, Republic of Moldova, [Republic of Georgia], Romania, Serbia, Slovak Republic, Slovenia, Spain, Sweden, Switzerland, Turkey, Ukraine, & United Kingdom

CONTENTS (general layout)

JAR-FSTD A

AEROPLANE FLIGHT SIMULATION TRAINING DEVICES

FOREWORD

CHECK LIST OF PAGES

PREAMBLE

SECTION 1 – REQUIREMENTS

SUBPART A	—	APPLICABILITY
SUBPART B	—	GENERAL
SUBPART C	—	AEROPLANE FLIGHT SIMULATION TRAINING DEVICES

SECTION 2 – ADVISORY CIRCULARS JOINT (ACJ)

ACJ B	—	GENERAL
ACJ C	—	AEROPLANE FLIGHT SIMULATION TRAINING DEVICES

1990

JAR-FSTD A

INTENTIONALLY LEFT BLANK

CONTENTS (details)
JAR-FSTD A
AEROPLANE FLIGHT SIMULATION TRAINING DEVICES

<i>Paragraph</i>		<i>Page</i>
SECTION 1 – REQUIREMENTS		
General and Presentation		1-0-1
SUBPART A – APPLICABILITY		
JAR-FSTD A.001	Applicability	1-A-1
SUBPART B – GENERAL		
JAR-FSTD A.005	Terminology	1-B-1
SUBPART C – AEROPLANE FLIGHT SIMULATION TRAINING DEVICES		
JAR-FSTD A.015	Application for FSTD Qualification	1-C-1
JAR-FSTD A.020	Validity FSTD Qualification	1-C-1
JAR-FSTD A.025	Rules governing FSTD Operators	1-C-1
JAR-FSTD A.030	Requirements for FSTDs qualified on or after 1 August 2008	1-C-2
JAR-FSTD A.031	Requirements for FFSs qualified on or after 1 April 1998 and before 1 August 2008	1-C-3
JAR-FSTD A.032	Requirements for FTDs qualified on or after 1 July 2000 and before 1 August 2008	1-C-3
JAR-FSTD A.033	Requirements for FNPTs qualified on or after 1 July 1999 and before 1 August 2008	1-C-3
JAR-FSTD A.034	Requirements for BITD qualified on or after 1 January 2003 and before 1 August 2008	1-C-3
JAR-FSTD A.035	Requirements for FFSs approved or qualified before 1 April 1998	1-C-3
JAR-FSTD A.036	Requirements for FTDs approved or qualified before 1 July 2000	1-C-4
JAR-FSTD A.037	Requirements for FNPTs approved or qualified before 1 July 1999	1-C-4
JAR-FSTD A.040	Changes to qualified FSTDs	1-C-4
JAR-FSTD A.045	Interim FSTD Qualification	1-C-5
JAR-FSTD A.050	Transferability of FSTD Qualification	1-C-5
Appendix 1 to JAR-FSTD A.030	FSTD Standards	1-C-7

JAR-FSTD A

<i>Paragraph</i>	<i>Page</i>
------------------	-------------

SECTION 2 – ADVISORY CIRCULARS JOINT (ACJ)

General and Presentation	2-0-1
--------------------------	-------

ACJ B – GENERAL

ACJ FSTD A.005	Terminology, Abbreviations	2-B-1
----------------	----------------------------	-------

ACJ C – AEROPLANE FSTDs

ACJ No. 1 to JAR-FSTD A.015	FSTD Qualification – Application and Inspection	2-C-1
ACJ No. 2 to JAR-FSTD A.015	FSTD Evaluations	2-C-6
ACJ FSTD A.020	Validity of an FSTD Qualification	2-C-10
ACJ No. 1 to JAR-FSTD A.025	Quality System	2-C-10
ACJ No. 2 to JAR-FSTD A.025	BITD Operators Quality System	2-C-17
ACJ No. 3 to JAR-FSTD A.025	Installations	2-C-18
ACJ No. 1 to JAR-FSTD A.030	FSTDs qualified on or after 1 August 2008	2-C-19
Appendix 1 to ACJ No. 1 to JAR-FSTD A.030	Validation Test Tolerances	2-C-112
Appendix 2 to ACJ No. 1 to JAR-FSTD A.030	Validation Data Roadmap	2-C-114
Appendix 3 to ACJ No. 1 to JAR-FSTD A.030	Data Requirements for Alternate Engines	2-C-116
Appendix 4 to ACJ No. 1 to JAR-FSTD A.030	Data Requirements for Alternate Avionics	2-C-118
Appendix 5 to ACJ No. 1 to JAR-FSTD A.030	Transport Delay Testing Method	2-C-119
Appendix 6 to ACJ No. 1 to JAR-FSTD A.030	Recurrent Evaluations – Validation Test Data Presentation	2-C-122
Appendix 7 to ACJ No. 1 to JAR-FSTD A.030	Applicability	2-C-123
Appendix 8 to ACJ No. 1 to JAR-FSTD A.030	General technical Requirements for FSTD Qualification Levels	2-C-125
ACJ No. 2 to JAR-FSTD A.030	Guidance on Design and Qualification of Level “A” Aeroplane FFSs	2-C-130
ACJ No. 3 to JAR-FSTD A.030	Guidance on Design and Qualification of FNPTs	2-C-132
ACJ No. 4 to JAR-FSTD A.030	Guidance on Design and Qualification of BITDs	2-C-136
ACJ No. 1 to JAR-FSTD A.030(c)(1)	Engineering Simulator Validation Data	2-C-140

1993

JAR-FSTD A

<i>Paragraph</i>		<i>Page</i>
ACJ No.2 to JAR-FSTD A.030(c)(1)	Engineering Simulator Validation Data – Approved Guidelines	2-C-141
ACJ to FSTD A.035	FFS Approved or Qualified before 1 April 1998	2-C-143
ACJ to FSTD A.036	FTD Approved or Qualified before 1 July 2000	2-C-145
ACJ to FSTD A.037	FNPT Approved or Qualified before 1 July 1999	2-C-146
ACJ to FSTD A.045	New Aeroplane FFS/FTD Qualification – Additional Information	2-C-147

INTENTIONALLY LEFT BLANK

1994

JAR-FSTD A

INTENTIONALLY LEFT BLANK

FOREWORD

- 1 The Civil Aviation Authorities of certain European countries have agreed common comprehensive and detailed aviation requirements, referred to as Joint Aviation Requirements (JARs), with a view to minimising Type Certification problems on joint ventures, to facilitate the export and import of aviation products, to make it easier for maintenance carried out in one European country to be accepted by the Civil Aviation Authority in another European country and to regulate commercial air transport operations.
- 2 JARs are recognised by the Civil Aviation Authorities of participating countries as an acceptable basis for showing compliance with their national codes.
- 3 The content has been prepared using the expertise available in this field as well as the ICAO Document 9625, the 'Manual for the Qualification of Flight Simulators' and added to where necessary by making use of existing European regulations and the Federal Aviation Requirements of the United States of America where acceptable.
- 4 JAR-FSTD A is issued with no National Variants. It may be felt that the document does not contain all of the detailed compliance and interpretative information which some Civil Aviation Authorities and Industry organisations would like to see. However, it is accepted that JAR-FSTD A should be applied in practice and the lessons learned embodied in future amendments. The Civil Aviation Authorities of the JAA are therefore committed to early amendment in the light of experience.
- 5 Future development of the requirements of JAR-FSTD A, including the commitment in Paragraph 4, will be in accordance with the JAA's Notice of Proposed Amendment (NPA) procedures. These procedures allow for the amendment of JAR-FSTD A to be proposed by any organisation or person.
- 6 The Civil Aviation Authorities have agreed they should not unilaterally initiate amendment of their national codes without having made a proposal for amendment of JAR-FSTD A in accordance with the agreed procedure.
- 7 Definitions and abbreviations of terms used in JAR-FSTD A that are considered generally applicable are contained in JAR-1, Definitions and Abbreviations. However, definitions and abbreviations of terms used in JAR-FSTD A that are specific to a Subpart of JAR-FSTD A are normally given in the Subpart concerned or, exceptionally, in the associated compliance or interpretative material.
- 8 Amendments to the text in JAR-FSTD A are issued as Replacement Pages. These show an effective date and have the same status and applicability as JAR-FSTD A from that date.
- 9 New, amended and corrected text will be enclosed within heavy brackets until a subsequent 'Amendment' is issued.
- 10 Comment/Response documents developed following Notices of Proposed Amendment (NPA) consultation have been produced by the JAA and are published on the JAA Internet Site: www.jaa.nl. Readers can also apply to JAA for copies of specific Comment/Response Documents as required.

1996

JAR-FSTD A

INTENTIONALLY LEFT BLANK

JOINT AVIATION REQUIREMENTS
CHECK LIST OF PAGES
JAR-FSTD A - AEROPLANE FLIGHT SIMULATION TRAINING DEVICES

Initial issue dated 01 May 2008

The following pages of JAR-FSTD A are now current:

<i>Page No</i>	<i>Legend</i>	<i>Date</i>
Title Page	Initial Issue	01.05.08
ii	Initial Issue	01.05.08
C-1	Initial Issue	01.05.08
C-2	Initial Issue	01.05.08
C-3	Initial Issue	01.05.08
C-4	Initial Issue	01.05.08
C-5	Initial Issue	01.05.08
C-6	Initial Issue	01.05.08
F-1	Initial Issue	01.05.08
F-2	Initial Issue	01.05.08
CL-1	Initial Issue	01.05.08
CL-2	Initial Issue	01.05.08
CL-3	Initial Issue	01.05.08
CL-4	Initial Issue	01.05.08
P-1	Initial Issue	01.05.08
P-2	Initial Issue	01.05.08
1-0-1	Initial Issue	01.05.08
1-0-2	Initial Issue	01.05.08
1-A-1	Initial Issue	01.05.08
1-A-2	Initial Issue	01.05.08
1-B-1	Initial Issue	01.05.08
1-B-2	Initial Issue	01.05.08
1-C-1	Initial Issue	01.05.08
1-C-2	Initial Issue	01.05.08
1-C-3	Initial Issue	01.05.08
1-C-4	Initial Issue	01.05.08
1-C-5	Initial Issue	01.05.08
1-C-6	Initial Issue	01.05.08
1-C-7	Initial Issue	01.05.08
1-C-8	Initial Issue	01.05.08
1-C-9	Initial Issue	01.05.08
1-C-10	Initial Issue	01.05.08
1-C-11	Initial Issue	01.05.08
1-C-12	Initial Issue	01.05.08
1-C-13	Initial Issue	01.05.08
1-C-14	Initial Issue	01.05.08
1-C-15	Initial Issue	01.05.08
1-C-16	Initial Issue	01.05.08
1-C-17	Initial Issue	01.05.08
1-C-18	Initial Issue	01.05.08

JAR-FSTD A

<i>Paragraph</i>	<i>Legend</i>	<i>Page</i>
1-C-19	Initial Issue	01.05.08
1-C-20	Initial Issue	01.05.08
1-C-21	Initial Issue	01.05.08
1-C-22	Initial Issue	01.05.08
1-C-23	Initial Issue	01.05.08
1-C-24	Initial Issue	01.05.08
1-C-25	Initial Issue	01.05.08
1-C-26	Initial Issue	01.05.08
1-C-27	Initial Issue	01.05.08
1-C-28	Initial Issue	01.05.08
1-C-29	Initial Issue	01.05.08
1-C-30	Initial Issue	01.05.08
2-0-1	Initial Issue	01.05.08
2-0-2	Initial Issue	01.05.08
2-B-1	Initial Issue	01.05.08
2-B-2	Initial Issue	01.05.08
2-B-3	Initial Issue	01.05.08
2-B-4	Initial Issue	01.05.08
2-B-5	Initial Issue	01.05.08
2-B-6	Initial Issue	01.05.08
2-B-7	Initial Issue	01.05.08
2-B-8	Initial Issue	01.05.08
2-C-1	Initial Issue	01.05.08
2-C-2	Initial Issue	01.05.08
2-C-3	Initial Issue	01.05.08
2-C-4	Initial Issue	01.05.08
2-C-5	Initial Issue	01.05.08
2-C-6	Initial Issue	01.05.08
2-C-7	Initial Issue	01.05.08
2-C-8	Initial Issue	01.05.08
2-C-9	Initial Issue	01.05.08
2-C-10	Initial Issue	01.05.08
2-C-11	Initial Issue	01.05.08
2-C-12	Initial Issue	01.05.08
2-C-13	Initial Issue	01.05.08
2-C-14	Initial Issue	01.05.08
2-C-15	Initial Issue	01.05.08
2-C-16	Initial Issue	01.05.08
2-C-17	Initial Issue	01.05.08
2-C-18	Initial Issue	01.05.08
2-C-19	Initial Issue	01.05.08
2-C-20	Initial Issue	01.05.08
2-C-21	Initial Issue	01.05.08
2-C-22	Initial Issue	01.05.08
2-C-23	Initial Issue	01.05.08
2-C-24	Initial Issue	01.05.08
2-C-25	Initial Issue	01.05.08
2-C-26	Initial Issue	01.05.08
2-C-27	Initial Issue	01.05.08
2-C-28	Initial Issue	01.05.08
2-C-29	Initial Issue	01.05.08
2-C-30	Initial Issue	01.05.08
2-C-31	Initial Issue	01.05.08
2-C-32	Initial Issue	01.05.08
2-C-33	Initial Issue	01.05.08
2-C-34	Initial Issue	01.05.08
2-C-35	Initial Issue	01.05.08
2-C-36	Initial Issue	01.05.08
2-C-37	Initial Issue	01.05.08
2-C-38	Initial Issue	01.05.08

<i>Paragraph</i>	<i>Legend</i>	<i>Page</i>
2-C-39	Initial Issue	01.05.08
2-C-40	Initial Issue	01.05.08
2-C-41	Initial Issue	01.05.08
2-C-42	Initial Issue	01.05.08
2-C-43	Initial Issue	01.05.08
2-C-44	Initial Issue	01.05.08
2-C-45	Initial Issue	01.05.08
2-C-46	Initial Issue	01.05.08
2-C-47	Initial Issue	01.05.08
2-C-48	Initial Issue	01.05.08
2-C-49	Initial Issue	01.05.08
2-C-50	Initial Issue	01.05.08
2-C-51	Initial Issue	01.05.08
2-C-52	Initial Issue	01.05.08
2-C-53	Initial Issue	01.05.08
2-C-54	Initial Issue	01.05.08
2-C-55	Initial Issue	01.05.08
2-C-56	Initial Issue	01.05.08
2-C-57	Initial Issue	01.05.08
2-C-58	Initial Issue	01.05.08
2-C-59	Initial Issue	01.05.08
2-C-60	Initial Issue	01.05.08
2-C-61	Initial Issue	01.05.08
2-C-62	Initial Issue	01.05.08
2-C-63	Initial Issue	01.05.08
2-C-64	Initial Issue	01.05.08
2-C-65	Initial Issue	01.05.08
2-C-66	Initial Issue	01.05.08
2-C-67	Initial Issue	01.05.08
2-C-68	Initial Issue	01.05.08
2-C-69	Initial Issue	01.05.08
2-C-70	Initial Issue	01.05.08
2-C-71	Initial Issue	01.05.08
2-C-72	Initial Issue	01.05.08
2-C-73	Initial Issue	01.05.08
2-C-74	Initial Issue	01.05.08
2-C-75	Initial Issue	01.05.08
2-C-76	Initial Issue	01.05.08
2-C-77	Initial Issue	01.05.08
2-C-78	Initial Issue	01.05.08
2-C-79	Initial Issue	01.05.08
2-C-80	Initial Issue	01.05.08
2-C-81	Initial Issue	01.05.08
2-C-82	Initial Issue	01.05.08
2-C-83	Initial Issue	01.05.08
2-C-84	Initial Issue	01.05.08
2-C-85	Initial Issue	01.05.08
2-C-86	Initial Issue	01.05.08
2-C-87	Initial Issue	01.05.08
2-C-88	Initial Issue	01.05.08
2-C-89	Initial Issue	01.05.08
2-C-90	Initial Issue	01.05.08
2-C-91	Initial Issue	01.05.08
2-C-92	Initial Issue	01.05.08
2-C-93	Initial Issue	01.05.08
2-C-94	Initial Issue	01.05.08
2-C-95	Initial Issue	01.05.08
2-C-96	Initial Issue	01.05.08
2-C-97	Initial Issue	01.05.08
2-C-98	Initial Issue	01.05.08
2-C-99	Initial Issue	01.05.08
2-C-100	Initial Issue	01.05.08
2-C-101	Initial Issue	01.05.08

JAR-FSTD A

<i>Paragraph</i>	<i>Legend</i>	<i>Page</i>
2-C-102	Initial Issue	01.05.08
2-C-103	Initial Issue	01.05.08
2-C-104	Initial Issue	01.05.08
2-C-105	Initial Issue	01.05.08
2-C-106	Initial Issue	01.05.08
2-C-107	Initial Issue	01.05.08
2-C-108	Initial Issue	01.05.08
2-C-109	Initial Issue	01.05.08
2-C-110	Initial Issue	01.05.08
2-C-111	Initial Issue	01.05.08
2-C-112	Initial Issue	01.05.08
2-C-113	Initial Issue	01.05.08
2-C-114	Initial Issue	01.05.08
2-C-115	Initial Issue	01.05.08
2-C-116	Initial Issue	01.05.08
2-C-117	Initial Issue	01.05.08
2-C-118	Initial Issue	01.05.08
2-C-119	Initial Issue	01.05.08
2-C-120	Initial Issue	01.05.08
2-C-121	Initial Issue	01.05.08
2-C-122	Initial Issue	01.05.08
2-C-123	Initial Issue	01.05.08
2-C-124	Initial Issue	01.05.08
2-C-125	Initial Issue	01.05.08
2-C-126	Initial Issue	01.05.08
2-C-127	Initial Issue	01.05.08
2-C-128	Initial Issue	01.05.08
2-C-129	Initial Issue	01.05.08
2-C-130	Initial Issue	01.05.08
2-C-131	Initial Issue	01.05.08
2-C-132	Initial Issue	01.05.08
2-C-133	Initial Issue	01.05.08
2-C-134	Initial Issue	01.05.08
2-C-135	Initial Issue	01.05.08
2-C-136	Initial Issue	01.05.08
2-C-137	Initial Issue	01.05.08
2-C-138	Initial Issue	01.05.08
2-C-139	Initial Issue	01.05.08
2-C-140	Initial Issue	01.05.08
2-C-141	Initial Issue	01.05.08
2-C-142	Initial Issue	01.05.08
2-C-143	Initial Issue	01.05.08
2-C-144	Initial Issue	01.05.08
2-C-145	Initial Issue	01.05.08
2-C-146	Initial Issue	01.05.08
2-C-147	Initial Issue	01.05.08
2-C-148	Initial Issue	01.05.08

PREAMBLE

JAR-FSTD A

Initial Issue

JAR-FSTD A comprises 3 Subparts (A, B and C) in Section 1, and 2 Subparts (B and C) in Section 2.

JAR-FSTD A is a simple amalgamation of JAR STD 1A, 2A, 3A and 4A into one document.

Section 1

Subpart C

Terminology and basic regulatory processes combined

Table of Standards in Appendix 1 to JAR-FSTD A.030 contains the standard for all devices

Section 2

Subpart B

Terminology and Abbreviations rationalised and harmonised with Aircraft STD standards documents.

Subpart C

Regulatory Processes combined.

Table of Objective Tests (ACJ to JAR-FSTD A.030) contains the testing requirements for all devices.

Table of Functions and Subjective Tests (ACJ to JAR-FSTD A.030) contains the testing requirements for all devices.

2002

JAR-FSTD A

INTENTIONALLY LEFT BLANK

SECTION 1

JAR-FSTD A

SECTION 1 – REQUIREMENTS

1 GENERAL

1.1 This Section contains the requirements for aeroplane Flight Simulation Training Devices.

2 PRESENTATION

- 2.1 The requirements of JAR–FSTD A are presented in two columns on loose pages, each page being identified by the date of issue and the Amendment number under which it is amended or reissued.
- 2.2 Sub-headings are in italic typeface.
- 2.3 Explanatory Notes not forming part of the requirements appear in smaller typeface.
- 2.4 New, amended and corrected text will be enclosed within heavy brackets until a subsequent 'Amendment' is issued.
- 2.5 After each paragraph, the various changes and amendments, if any since the initial issue, are indicated together with their date of issue.

2004

JAR-FSTD A

SECTION 1

INTENTIONALLY LEFT BLANK

SECTION 1

JAR-FSTD A

SUBPART A – APPLICABILITY

JAR-FSTD A.001 Applicability

JAR-FSTD A as amended applies to those persons, organisations or enterprises (Flight Simulation Training Devices (FSTD) operators) or, in the case of BITDs only, manufacturers seeking initial qualification of FSTDs.

The version of JAR-FSTD A agreed by the Authority and used for issue of the initial qualification shall be applicable for future recurrent qualifications of the FSTD unless recategorised.

FSTD users shall also gain approval to use the FSTD as part of their approved training programmes despite the fact that the FSTD has been previously qualified.

INTENTIONALLY LEFT BLANK

INTENTIONALLY LEFT BLANK

2006

JAR-FSTD A

SECTION 1

INTENTIONALLY LEFT BLANK

SECTION 1
JAR-FSTD A
SUBPART B - GENERAL
JAR-FSTD A.005 Terminology

(See ACJ to FSTD A.005)

Because of the technical complexity of FSTD qualification, it is essential that standard terminology is used throughout. The following principal terms and abbreviations shall be used in order to comply with JAR-FSTD (A). Further terms and abbreviations are contained in ACJ to FSTD A.005.

(a) *Flight Simulation Training Device (FSTD)*. A training device which is a Full Flight Simulator (FFS), a Flight Training Device (FTD), a Flight & Navigation Procedures Trainer (FNPT), or a Basic Instrument Training Device (BITD).

(b) *Full Flight Simulator (FFS)*. A full size replica of a specific type or make, model and series aeroplane flight deck, including the assemblage of all equipment and computer programmes necessary to represent the aeroplane in ground and flight operations, a visual system providing an out of the flight deck view, and a force cueing motion system. It is in compliance with the minimum standards for FFS Qualification.

(c) *Flight Training Device (FTD)*. A full size replica of a specific aeroplane type's instruments, equipment, panels and controls in an open flight deck area or an enclosed aeroplane flight deck, including the assemblage of equipment and computer software programmes necessary to represent the aeroplane in ground and flight conditions to the extent of the systems installed in the device. It does not require a force cueing motion or visual system. It is in compliance with the minimum standards for a specific FTD Level of Qualification.

(d) *Flight and Navigation Procedures Trainer (FNPT)*. A training device which represents the flight deck or cockpit environment including the assemblage of equipment and computer programmes necessary to represent an aeroplane or class of aeroplane in flight operations to the extent that the systems appear to function as in an aeroplane. It is in compliance with the minimum standards for a specific FNPT Level of Qualification.

(e) *Basic Instrument Training Device (BITD)*. A ground based training device which represents the student pilot's station of a class of aeroplanes. It may use screen based instrument panels and springloaded flight controls, providing a training platform for at least the procedural aspects of instrument flight.

(f) *Other Training Device (OTD)*. A training aid other than FFS, FTD, FNPT or BITD which provides

(JAR-FSTD A.005 continued)

for training where a complete flight deck environment is not necessary.

(g) *Flight Simulation Training Device User Approval (FSTD User Approval)*. The extent to which an FSTD of a specified Qualification Level may be used by persons, organisations or enterprises as approved by the Authority. It takes account of aeroplane to FSTD differences and the operating and training ability of the organisation.

(h) *Flight Simulation Training Device Operator (FSTD operator)*. That person, organisation or enterprise directly responsible to the Authority for requesting and maintaining the qualification of a particular FSTD.

(i) *Flight Simulation Training Device User (FSTD User)*. The person, organisation or enterprise requesting training, checking and testing credits through the use of an FSTD.

(j) *Flight Simulation Training Device Qualification (FSTD Qualification)*. The level of technical ability of an FSTD as defined in the compliance document.

(k) *BITD Manufacturer*. That organisation or enterprise being directly responsible to the Authority for requesting the initial BITD model qualification.

(l) *BITD Model*. A defined hardware and software combination, which has obtained a qualification. Each BITD will equate to a specific model and be a serial numbered unit.

(m) *Qualification Test Guide (QTG)*. A document designed to demonstrate that the performance and handling qualities of an FSTD agree within prescribed limits with those of the aeroplane and that all applicable regulatory requirements have been met. The QTG includes both the aeroplane and FSTD data used to support the validation.

INTENTIONALLY LEFT BLANK

2008

JAR-FSTD A

SECTION 1

INTENTIONALLY LEFT BLANK

SECTION 1
JAR-FSTD A
SUBPART C – AEROPLANE FLIGHT SIMULATION TRAINING DEVICES

JAR-FSTD A.015 Application for FSTD Qualification
 (See ACJ No. 1 to JAR-FSTD A.015)
 (See ACJ No. 2 to JAR-FSTD A.015)

- (a) The FSTD operator requiring evaluation of a FFS, FTD or FNPT shall apply to the Authority giving 3 months notice. In exceptional cases this period may be reduced to one month at the discretion of the Authority.
- (b) An FSTD Qualification Certificate will be issued following satisfactory completion of an evaluation of the FFS, FTD or FNPT by the Authority.
- (c) For BITDs the manufacturer of a new BITD model which requires evaluation shall apply to the Authority giving 3 months notice. In exceptional cases this period may be reduced to one month at the discretion of the Authority.
- (d) A BITD Qualification Certificate will be issued for the BITD model to the manufacturer following satisfactory completion of an initial evaluation by the Authority. This qualification certificate is valid for any devices manufactured to this standard without the need for the device to be subjected to further technical evaluation. The BITD model must clearly be identified by a BITD model number.
- (e) The numbering of the BITD model must clearly define the hardware and software configuration of the qualified BITD model. A running serial number shall follow the BITD model identification number.

JAR-FSTD A.020 Validity of FSTD Qualification
 (See ACJ to JAR-FSTD A.020)

- (a) An FSTD qualification is valid for 12 months unless otherwise specified by the Authority.
- (b) An FSTD qualification revalidation can take place at any time within the 60 days prior to the expiry of the validity of the qualification document. The new period of validity shall continue from the expiry date of the previous qualification document.
- (c) The Authority shall refuse, revoke, suspend or vary an FSTD qualification, if the provisions of JAR-FSTD A are not satisfied.

JAR-FSTD A.020(d) (continued)

(d) The qualification of each BITD model serial number is valid for 36 months from the commencement of operation, unless reduced by the Authority. It is the operator's responsibility to apply for the revalidation of the qualification.

JAR-FSTD A.025 Rules Governing FSTD Operators

(See ACJ No. 1 to JAR-FSTD A.025)
 (See ACJ No. 2 to JAR-FSTD A.025)
 (See ACJ No. 3 to JAR-FSTD A.025)

The FSTD operator shall demonstrate his capability to maintain the performance, functions and other characteristics specified for the FSTD Qualification Level as follows:

- (a) Quality System
 - (1) A Quality System shall be established and a Quality Manager designated to monitor compliance with, and the adequacy of, procedures required to ensure the maintenance of the Qualification Level of FSTDs. Compliance monitoring shall include a feedback system to the Accountable Manager to ensure corrective action as necessary.
 - (2) The Quality System shall include a Quality Assurance Programme that contains procedures designed to verify that the specified performance, functions and characteristics are being conducted in accordance with all applicable requirements, standards and procedures.
 - (3) The Quality System and the Quality Manager shall be acceptable to the Authority.
 - (4) The Quality System shall be described in relevant documentation.
- (b) Updating. A link shall be maintained between the operator's organization, the Authority and the relevant manufacturers to incorporate important modifications, especially:
 - (1) Aeroplane modifications that are essential for training and checking shall be introduced into all affected FSTDs whether or not enforced by an airworthiness directive.
 - (2) Modification of FSTDs, including motion and visual systems (where applicable):

JAR-FSTD A

JAR-FSTD A.025(b) (continued)

(i) When essential for training and checking, FSTD operators shall update their FSTDs (for example in the light of data revisions). Modifications of the FSTD hardware and software that affect handling, performance and systems operation or any major modifications of the motion or visual system shall be evaluated to determine the impact on the original qualification criteria. FSTD operators shall prepare amendments for any affected validation tests. The FSTD operator shall test the FSTD to the new criteria.

(ii) The Authority shall be advised in advance of any major changes to determine if the tests carried out by the FSTD operator are satisfactory. A special evaluation of the FSTD may be necessary prior to returning it to training following the modification.

(3) BITD operators shall maintain a link between their own organisation, the Authority and the BITD manufacturer to incorporate important modifications.

(c) Installations. Ensure that the FSTD is housed in a suitable environment that supports safe and reliable operation.

(1) The FSTD operator shall ensure that the FSTD and its installation comply with the local regulations for health and safety. However, as a minimum all FSTD occupants and maintenance personnel shall be briefed on FSTD safety to ensure that they are aware of all safety equipment and procedures in the FSTD in case of emergency.

(2) The FSTD safety features such as emergency stops and emergency lighting shall be checked at least annually and recorded by the FSTD operator.

(d) Additional Equipment. Where additional equipment has been added to the FSTD, even though not required for qualification, it will be assessed to ensure that it does not adversely affect the quality of training. Therefore any subsequent modification, removal or unserviceability could affect the qualification of the device.

SECTION 1
JAR-FSTD A.030 Requirements for FSTD qualified on or after 1 August 2008

(See Appendix 1 to JAR-FSTD A.030)

(See ACJ No. 1 to JAR-FSTD A.030)

(See ACJ No. 2 to JAR-FSTD A.030)

(See ACJ No. 3 to JAR-FSTD A.030)

(See ACJ No. 4 to JAR-FSTD A.030)

(See ACJ No. 1 to JAR-FSTD A.030(c)(1))

(See ACJ No. 2 to JAR-FSTD A.030(c)(1))

(a) Any FSTD submitted for initial evaluation on or after 1 August 2008 will be evaluated against applicable JAR-FSTD A criteria for the Qualification Levels applied for. Recurrent evaluations of a FSTD will be based on the same version of JAR-FSTD A that was applicable for its initial evaluation. An upgrade will be based on the currently applicable version of JAR-FSTD A.

(b) A FSTD shall be assessed in those areas that are essential to completing the flight crewmember training and checking process as applicable.

(c) The FSTD shall be subjected to:

(1) Validation tests and

(2) Functions & subjective tests

(d) Data shall be of a standard that satisfies the Authority before the FSTD can gain a Qualification Level.

(e) The FSTD operator shall submit a QTG in a form and manner that is acceptable to the Authority.

(f) The QTG will only be approved after completion of an initial or upgrade evaluation, and when all the discrepancies in the QTG have been addressed to the satisfaction of the Authority. After inclusion of the results of the tests witnessed by the Authority, the approved QTG becomes the Master QTG (MQTG), which is the basis for the FSTD qualification and subsequent recurrent FSTD evaluations. A copy of the MQTG shall be delivered by the BITD manufacturer together with any BITD model delivered to an Operator.

(g) The FSTD operator shall:

(1) Run the complete set of tests contained within the MQTG progressively between each annual evaluation by the Authority. Results shall be dated and retained in

SECTION 1

JAR-FSTD A.030(g) (continued)

order to satisfy both the FSTD operator and the Authority that FSTD standards are being maintained; and

(2) Establish a Configuration Control System to ensure the continued integrity of the hardware and software of the qualified FSTD.

JAR-FSTD A.031 Requirements for FFS qualified on or after 1 April 1998 and before 1 August 2008

Any FFS submitted for initial evaluation on or after 1 April 1998 and before 1 August 2008, shall automatically be granted an equivalent qualification under JAR-FSTD A with effect from the re-evaluation conducted at the end of the current validity period. This re-evaluation, and all future re-evaluations, will be conducted in accordance with the requirements of the same version of JAR-STD 1A, which was applicable for its last evaluation prior to implementation of JAR-FSTD A. Any upgrade will be based on the currently applicable version of JAR-FSTD A.

JAR-FSTD A.032 Requirements for Flight Training Devices (FTD) qualified on or after 1 July 2000 and before 1 August 2008

Any FTD submitted for initial evaluation on or after 1 January 2000 and before 1 August 2008, shall automatically be granted an equivalent qualification under JAR-FSTD A with effect from the re-evaluation conducted at the end of the current validity period. This re-evaluation, and all future re-evaluations, will be conducted in accordance with of the same version of JAR-STD 2A, which was applicable for its last evaluation prior to implementation of JAR-FSTD A. Any upgrade will be based on the currently applicable version of JAR-FSTD A.

JAR-FSTD A.033 Requirements for Flight & Navigation Procedures Trainers (FNPT) qualified on or after 1 July 1999 and before 1 August 2008

Any FNPT submitted for initial evaluation on or after 1 July 1999 and before 1 August 2008, shall automatically be granted an equivalent qualification under JAR-FSTD A with effect from the re-evaluation conducted at the end of the

JAR-FSTD A

JAR-FSTD A.033 (continued)

current validity period. This re-evaluation, and all future re-evaluations, will be conducted in accordance with the requirements of the same version of JAR-STD 3A, which was applicable for its last evaluation prior to implementation of JAR-FSTD A. Any upgrade will be based on the currently applicable version of JAR-FSTD A.

JAR-FSTD A.034 Requirements for Basic Instrument Training Devices (BITD) qualified on or after 1 January 2003 and before 1 August 2008

Any BITD submitted for initial evaluation on or after 1 January 2003 and before 1 August 2008, shall automatically be granted an equivalent qualification under JAR-FSTD A with effect from the re-evaluation conducted at the end of the current validity period. This re-evaluation, and all future re-evaluations, will be conducted in accordance with the requirements of the same version of JAR-STD 4A, which was applicable for its last evaluation prior to implementation of JAR-FSTD A. Any upgrade will be based on the currently applicable version of JAR-FSTD A.

JAR-FSTD A.035 Requirements for Full Flight Simulators approved or qualified before 1 April 1998 (See ACJ to JAR-FSTD A.035)

(a) FFS approved or qualified in accordance with national regulations of JAA Member States before 1 April 1998 will either be recategorised or will continue to maintain their approval under the Grandfather Rights provision, in accordance with sub-paragraphs (c) and (d) below. For FFS that are not re-categorized, maximum credit shall under no circumstances exceed originally issued National credits.

(b) FFS's, neither previously recategorised nor with an approval maintained under the Grandfather Rights provision, will be qualified in accordance with JAR-FSTD A.030.

(c) FFS that are not recategorised but that have a primary reference document used for their testing, may be qualified by the Authority to an equivalent JAR-FSTD A Qualification Level, either AG, BG, CG or DG. An upgrade requires the recategorisation of the FFS.

(1) To gain and maintain an equivalent Qualification Level, these FFS shall be assessed

JAR-FSTD A
JAR-FSTD A.035(c) (continued)

in those areas that are essential to completing the flight crewmember training and checking process, as applicable.

(2) The FFS shall be subjected to:

- (i) Validation tests; and
- (ii) Functions and subjective tests.

(d) FFS that are not recategorised and that do not have a primary reference document used for their testing shall be qualified by special arrangement. Such FFS will be issued with a Special Category and shall be subjected to functions and subjective tests corresponding to those detailed in this document. In addition any previously recognised validation test shall be used.

JAR-FSTD A.036 Requirements for Flight Training Devices approved or qualified before 1 July 2000
 (See ACJ to JAR-FSTD A.036)

(a) FTDs approved or qualified in accordance with national regulations of JAA Members States before 1 July 2000 either will be recategorised or will continue to maintain their approval under the Grandfather Rights provision, in accordance with JAR-FSTD A.036(c) and JAR-FSTD A.036 (d).

(b) FTDs, neither previously recategorised nor with an approval maintained under the Grandfather Rights provision, will be qualified in accordance with JAR-FSTD A.030.

(c) FTDs that are not recategorised but that have a primary reference document used for their testing may be qualified by the Authority to an equivalent JAR-FSTD Qualification Level, either 1G or 2G. These Qualification Levels refer to similar credits achieved by JAR-FSTD A Level 1 and 2.

(1) To gain and maintain an equivalent Qualification Level, these FTDs shall be assessed in those areas which are essential to completing the flight crew member training and checking process, including:

- (i) Longitudinal, lateral and directional handling qualities (where applicable);
- (ii) Performance on the ground and in the air;
- (iii) Specific operations where applicable;
- (iv) Flight deck configuration;

SECTION 1
JAR-FSTD A.036 (continued)

(v) Functioning during normal, abnormal, emergency and, where applicable non normal operation;

(vi) Instructor station function and FTD control, and

(vii) Certain additional requirements depending on the Qualification Level and the installed equipment.

(2) The FTD shall be subjected to:

- (i) Validation Tests, and
- (ii) Functions and Subjective Tests.

(d) FTDs that are not recategorised and that do not have a primary reference document used for their testing shall be qualified by special arrangement.

(1) Such FTDs will be issued with Special Categories.

(2) These FTDs shall be subjected to the same Functions and Subjective Tests referred to in JAR-FSTD A.036(c) (2) (ii).

(3) In addition any previously recognised Validation Test shall be used.

JAR-FSTD A.037 Requirements for Flight Navigation and Procedures Trainers approved or qualified before 1 July 1999
 (See ACJ to JAR-FSTD A.037)

(No Longer Applicable)

JAR-FSTD A.040 Changes to qualified FSTD

(a) *Requirement to notify major changes to a FSTD.* The operator of a qualified FSTD shall inform the Authority of proposed major changes such as:

(1) Aeroplane modifications, which could affect FSTD qualification.

(2) FSTD hardware and or software modifications that could affect the handling qualities, performances or system representations.

(3) Relocation of the FSTD; and

(4) Any deactivation of the FSTD.

SECTION 1

JAR-FSTD A

JAR-FSTD A.040 (continued)

The Authority may complete a special evaluation following major changes or when a FSTD appears not to be performing at its initial Qualification Level.

(b) *Upgrade of a FSTD.* A FSTD may be upgraded to a higher Qualification Level. Special evaluation is required before the award of a higher Level of Qualification.

(1) If an upgrade is proposed the FSTD operator shall seek the advice of the Authority and give full details of the modifications. If the upgrade evaluation does not fall upon the anniversary of the original qualification date, a special evaluation is required to permit the FSTD to continue to qualify even at the previous Qualification Level.

(2) In the case of a FSTD upgrade, an FSTD operator shall run all validation tests for the requested Qualification Level. Results from previous evaluations shall not be used to validate FSTD performance for the current upgrade.

(c) Relocation of a FSTD

(1) In instances where a FSTD is moved to a new location, the Authority shall be advised before the planned activity along with a schedule of related events.

(2) Prior to returning the FSTD to service at the new location, the FSTD operator shall perform at least one third of the validation tests and, functions and subjective tests to ensure that the FSTD performance meets its original qualification standard. A copy of the test documentation shall be retained together with the FSTD records for review by the Authority.

(3) An evaluation of the FSTD in accordance with its original JAA qualification criteria shall be at the discretion of the Authority.

(d) Deactivation of a currently qualified FSTD

(1) If a FSTD operator plans to remove a FSTD from active status for prolonged periods, the Authority shall be notified and suitable controls established for the period during which the FSTD is inactive.

(2) The FSTD operator shall agree a procedure with the Authority to ensure that the FSTD can be restored to active status at its original Qualification Level.

JAR-FSTD A.045 Interim FSTD Qualification (See ACJ to FSTD A.045)

(a) In case of new aeroplane programmes, special arrangements shall be made to enable an interim Qualification Level to be achieved.

(b) For Full Flight Simulators, an Interim Qualification Level will only be granted at levels A, B or C.

(c) Requirements, details relating to the issue, and the period of validity of an interim Qualification Level will be decided by the Authority.

JAR-FSTD A.050 Transferability of FSTD Qualification

When there is a change of FSTD operator:

(a) The new FSTD operator shall advise the Authority in advance in order to agree upon a plan of transfer of the FSTD.

(b) At the discretion of the Authority, the FSTD shall be subject to an evaluation in accordance with its original JAA qualification criteria.

(c) Provided that the FSTD performs to its original standard, its original Qualification Level shall be restored. Revised user approval(s) may also be required.

INTENTIONALLY LEFT BLANK

2014

JAR-FSTD A

SECTION 1

INTENTIONALLY LEFT BLANK

SECTION 1
JAR-FSTD A
Appendix 1 to JAR-FSTD A.030
Flight Simulation Training Device Standards

This appendix describes the minimum Full Flight Simulator (FFS), Flight Training Device (FTD), Flight and Navigation Procedures Trainer (FNPT) and Basic Instrument Training Devices (BITD) requirements for qualifying devices to the required Qualification Levels. Certain requirements included in this section shall be supported with a statement of compliance (SOC) and, in some designated cases, an objective test. The SOC will describe how the requirement was met. The test results shall show that the requirement has been attained. In the following tabular listing of FSTD standards, statements of compliance are indicated in the compliance column.

For FNPT use in Multi-Crew Co-operation (MCC) training the general technical requirement are expressed in the MCC column with additional systems, instrumentation and indicators as required for MCC training and operation.

For MCC (Multi Crew Co-operation) minimum technical requirements are as for Level II, with the following additions or amendments:

1	Turbo-jet or turbo-prop engines.
2	Performance reserves, in case of an engine failure, to be in accordance with JAR-25. These may be simulated by a reduction in the aeroplane gross mass.
3	Retractable landing gear.
4	Pressurisation system.
5	De-icing systems
6	Fire detection / suppression system
7	Dual controls
8	Autopilot with automatic approach mode
9	2 VHF transceivers including oxygen masks intercom system
10	2 VHF NAV receivers (VOR, ILS, DME)
11	1 ADF receiver
12	1 Marker receiver
13	1 transponder
The following indicators shall be located in the same positions on the instrument panels of both pilots:	
1	Airspeed
2	Flight attitude with flight director
3	Altimeter
4	Flight director with ILS (HSI)
5	Vertical speed
6	ADF
7	VOR
8	Marker indication (as appropriate)
9	Stop watch (as appropriate)

INTENTIONALLY LEFT BLANK

JAR-FSTD A

Appendix 1 to JAR-FSTD A.030 (continued)

SECTION 1

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS		FFS LEVEL			FTD LEVEL			FNPT LEVEL			BITD		COMPLIANCE
		A	B	C	D	1	2	I	II	MCC			
1.1 General		✓	✓	✓				✓	✓	✓	✓	✓	
a.1 A fully enclosed flight deck													
a.2 A cockpit/flight deck sufficiently enclosed to exclude distraction, which will replicate that of the aeroplane or class of aeroplane simulated													
a.3 Flight deck, a full scale replica of the aeroplane simulated.		✓	✓	✓				✓	✓	✓	✓	✓	
		Equipment for operation of the cockpit windows shall be included in the FSTD, but the actual windows need not be operable. The flight deck, for FSTD purposes, consists of all that space forward of a cross section of the fuselage at the most extreme aft setting of the pilots' seats. Additional required flight crewmember duty stations and those required bulkheads aft of the pilot seats are also considered part of the flight deck and shall replicate the aeroplane.											
		Bulkheads containing items such as switches, circuit breakers, supplementary radio panels, etc. to which the flight crew may require access during any event after pre-flight cockpit preparation is complete are considered essential and may not be omitted. Bulkheads containing only items such as landing gear pin storage compartments, fire axes or extinguishers, spare light bulbs, aircraft document pouches etc. are not considered essential and may be omitted. Such items, or reasonable facsimile, shall still be available in the FSTD but may be relocated to a suitable location as near as practical to the original position. Fire axes and any similar purpose instruments need only be represented in silhouette.											
a.4 Direction of movement of controls and switches identical to that in the aeroplane.		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	

SECTION 1

Appendix 1 to JAR-FSTD A.030 (continued)

	FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL				FTD LEVEL	FNPT LEVEL	B1TD	COMPLIANCE
		A	B	C	D				
1.1	General								
a.5	A full size panel of replicated system(s) which will have actuation of controls and switches that replicate those of the aeroplane simulated.					✓	✓		The use of electronically displayed images with physical overlay incorporating operable switches, knobs, buttons replicating aeroplane instruments panels may be acceptable.
a.6	Cockpit/flight deck switches, instruments, equipment, panels, systems, primary and secondary flight controls sufficient for the training events to be accomplished shall be located in a spatially correct flight deck area and will operate as, and represent those in, that aeroplane or class of aeroplane.					✓	✓	✓	For Multi-Crew Co-operation (MCC) qualification additional instrumentation and indicators may be required. See table at start of this appendix. For B1TDs the switches and controls size and shape and their location in the cockpit shall be representative.
a.7	Crew members seats shall be provided with sufficient adjustment to allow the occupant to achieve the design eye reference position appropriate to the aeroplane or class of aeroplane and for the visual system to be installed to align with that eye position.					✓	✓	✓	
b.1	Circuit breakers that affect procedures and/or result in observable cockpit indications properly located and functionally accurate.					✓	✓	✓	

JAR-FSTD A

Appendix 1 to JAR-FSTD A.030 (continued)

SECTION 1

	FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL				FTD LEVEL		FNPT LEVEL		BITD		COMPLIANCE
		A	B	C	D	1	2	I	II	MCC		
1.1 General		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	For FTD Levels 1 and 2 aerodynamic modelling sufficient to permit accurate systems operation and indication is acceptable. For FNPTs and BITDs class specific modelling is acceptable.
c.1	Flight dynamics model that accounts for various combinations of drag and thrust normally encountered in flight corresponding to actual flight conditions, including the effect of change in aeroplane attitude, sideslip, thrust, drag, altitude, temperature, gross weight, moments of inertia, centre of gravity location, and configuration.											
d.1	All relevant instrument indications involved in the simulation of the applicable aeroplane shall automatically respond to control movement by a flight crewmember or induced disturbance to the simulated aeroplane; e.g., turbulence or wind shear.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	For FNPTs instrument indications sufficient for the training events to be accomplished. Reference ACJ No. 3 to JAR-FSTD A.030.
												For BITDs instrument indications sufficient for the training events to be accomplished. Reference ACJ No. 4 to JAR-FSTD A.030.
d.2	Lighting environment for panels and instruments shall be sufficient for the operation being conducted.					✓	✓	✓	✓	✓	✓	For FTD Level 2 lighting environment shall be as per aeroplane.
e.1	Communications, navigation, and caution and warning equipment corresponding to that installed in the applicant's aeroplane with operation within the tolerances prescribed for the applicable airborne equipment.	✓	✓	✓	✓							For FTD 1 applies where the appropriate systems are replicated.
e.2	Navigation equipment corresponding to that of the replicated aeroplane or class of aeroplanes, with operation within the tolerances prescribed for the actual airborne equipment. This shall include communication equipment (telephone and air/ground communications systems).					✓	✓	✓	✓	✓	✓	

SECTION 1

Appendix 1 to JAR-FSTD A.030 (continued)

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL				FTD LEVEL		FNPT LEVEL		BITD		COMPLIANCE
	A	B	C	D	1	2	I	II	MCC		
1.1 General	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	For FTD 1 applies where navigation equipment is replicated.
e.3 Navigational data with the corresponding approach facilities. Navigation aids should be usable within range without restriction.											For all FFSs and FTDs 2 where used for area or airfield competence training or checking, navigation data should be updated within 28 days.
											For FNPTs and BITDs complete navigational data for at least 5 different European airports with corresponding precision and non-precision approach procedures including current updating within a period of 3 months.
f.1 In addition to the flight crewmember duty stations, three suitable seats for the instructor, delegated examiner and Authority inspector. The Authority will consider options to this standard based on unique cockpit configurations. These seats shall provide adequate vision to the pilot's panel and forward windows. Observer seats need not represent those found in the aeroplane but in the case of FSTDs fitted with a motion system, the seats shall be adequately secured to the floor of the FSTD, fitted with positive restraint devices and be of sufficient integrity to safely restrain the occupant during any known or predicted motion system excursion.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	For FTDs and FNPTs suitable seating arrangements for the Instructor and Examiner or Authority's Inspector should be provided.
											For BITDs suitable viewing arrangements for the Instructor should be provided.

JAR-FSTD A

Appendix 1 to JAR-FSTD A.030 (continued)

SECTION 1

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL				FTD LEVEL			FNPT LEVEL		BITD		COMPLIANCE
	A	B	C	D	1	2	I	II	MCC			
1.1 General												
g.1 FSTD systems shall simulate applicable aeroplane system operation, both on the ground and in flight. Systems shall be operative to the extent that all normal, abnormal, and emergency operating procedures can be accomplished.	✓	✓	✓	✓	✓	✓	✓	✓	✓			For FTD Level 1, applies where system is simulated. For FNPTs systems shall be operative to the extent that it shall be possible to perform all normal, abnormal and emergency operations as may be appropriate to the aeroplane or class of aeroplanes being simulated and as required for the training.
h.1 Instructor controls shall enable the operator to control all required system variables and insert abnormal or emergency conditions into the aeroplane systems.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Where applicable and as required for training the following shall be available : Position and flight freeze. A facility to enable the dynamic plotting of the flight path on approaches, commencing at the final approach fix, including the vertical profile Hard copy of map and approach plot

SECTION 1

Appendix 1 to JAR-FSTD A.030 (continued)

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL				FTD LEVEL		FNPT LEVEL		BITD		COMPLIANCE
	A	B	C	D	1	2	I	II	MCC		
1.1 General	✓	✓	✓	✓			✓	✓	✓	✓	
i.1 Control forces and control travel shall correspond to that of the replicated aeroplane. Control forces shall react in the same manner as in the aeroplane under the same flight conditions.											For FTD Level 2 Control forces and control travel should correspond to that of the replicated aeroplane with CT&M. It is not intended that the device should be flown manually other than for short periods when the autopilot is temporarily disengaged. For FNPT Level I and BITDs control forces and control travel shall broadly correspond to that of the replicated aeroplane or class of aeroplane. Control force changes due to an increase/decrease in aircraft speed are not necessary. In addition for FNPT Level II and MCC control forces and control travels shall respond in the same manner under the same flight conditions as in the aeroplane or class of aeroplane being simulated.

JAR-FSTD A

Appendix 1 to JAR-FSTD A.030 (continued)

SECTION 1

	FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL			FTD LEVEL			FNPT LEVEL			BITD	COMPLIANCE
		A	B	C	D	1	2	I	II	MCC		
j.1	1.1 General	✓	✓	✓	✓			✓	✓			
	j.1 Ground handling and aerodynamic programming shall include:											
(1)	Ground Effect. For example: round-out, flare, and touchdown. This requires data on lift, drag, pitching moment, trim, and power ground effect.											
(2)	Ground reaction – reaction of the aeroplane upon contact with the runway during landing to include strut deflections, tyre friction, side forces, and other appropriate data, such as weight and speed, necessary to identify the flight condition and configuration.											
(3)	Ground handling characteristics – steering inputs to include crosswind, braking, thrust reversing, deceleration and turning radius.											

SECTION 1

Appendix 1 to JAR-FSTD A.030 (continued)

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL						FTD LEVEL	FNPT LEVEL	BITD	COMPLIANCE
	A	B	C	D	1	2				
1.1 General										
k.1 Windshear models shall provide training in the specific skills required for recognition of wind shear phenomena and execution of recovery manoeuvres. Such models shall be representative of measured or accident derived winds, but may include simplifications which ensure repeatable encounters. For example, models may consist of independent variable winds in multiple simultaneous components. Wind models shall be available for the following critical phases of flight:			✓	✓						
(1) Prior to take-off rotation										
(2) At lift-off										
(3) During initial climb										
(4) Short final approach										
i.1 Instructor controls for environmental effects including wind speed and direction shall be provided.			✓	✓	✓	✓	✓	✓	✓	For FTDs environment modelling sufficient to permit accurate systems operation and indication.

JAR-FSTD A

Appendix 1 to JAR-FSTD A.030 (continued)

SECTION 1

	FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL			FTD LEVEL			FNPT LEVEL			BITD	COMPLIANCE
		A	B	C	D	1	2	I	II	MCC		
1.1 General	m.1 Stopping and directional control forces shall be representative for at least the following runway conditions based on aeroplane related data:											Statement of Compliance required.
(1) Dry		✓										Objective Tests required for (1), (2), (3), Subjective check for (4), (5), (6).
(2) Wet												
(3) Icy												
(4) Patchy wet												
(5) Patchy icy												
(6) Wet on rubber residue in touchdown zone.												
n.1 Brake and tyre failure dynamics (including antiskid) and decreased brake efficiency due to brake temperatures shall be representative and based on aeroplane related data.		✓	✓									Statement of Compliance required. Subjective test is required for decreased braking efficiency due to brake temperature, if applicable.
o.1 A means for quickly and effectively conducting daily testing of FSTD programming and hardware shall be available.		✓	✓									Statement of Compliance required.
p.1 Computer capacity, accuracy, resolution, and dynamic response shall be sufficient to fully support the overall fidelity, including its evaluation and testing.		✓	✓	✓	✓	✓	✓	✓	✓			Statement of Compliance required.

SECTION 1

Appendix 1 to JAR-FSTD A.030 (continued)

JAR-FSTD A

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS		FFS LEVEL			FTD LEVEL			FNPT LEVEL			BITD		COMPLIANCE
		A	B	C	D	1	2	I	II	MCC			
1.1	General												
q.1	Control feel dynamics shall replicate the aeroplane simulated.												Tests required.
	Free response of the controls shall match that of the aeroplane within the tolerances specified. Initial and upgrade evaluations will include control free response (pitch, roll and yaw controller) measurements recorded at the controls. The measured responses shall correspond to those of the aeroplane in take-off, cruise, and landing configurations.												
	(1) For aeroplanes with irreversible control systems, measurements may be obtained on the ground if proper pilot static inputs are provided to represent conditions typical of those encountered in flight. Engineering validation or aeroplane manufacturer rationale will be submitted as justification to ground test or omit a configuration.												
	(2) For FSTDs requiring static and dynamic tests at the controls, special test fixtures will not be required during initial evaluation if the FSTD operator's MQTG shows both test fixture results and alternate test method results such as computer data plots, which were obtained concurrently. Repetition of the alternate method during initial evaluation may then satisfy this requirement.												

JAR-FSTD A

Appendix 1 to JAR-FSTD A.030 (continued)

SECTION 1

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS			FFS LEVEL		FTD LEVEL		FNPT LEVEL		BITD		COMPLIANCE	
			A	B	C	D	1	2	I	II	MCC	
1.1 General			✓	✓	✓	✓	✓	✓	✓	✓	✓	Tests required.
r.1	One of the following two methods is acceptable as a means to prove compliance:											For Level 'A' & 'B' FFSs, and applicable systems for FTDs, FNPTs and BITDs the maximum permissible delay is 300 milliseconds.
	<p>(1) Transport Delay: A transport delay test may be used to demonstrate that the FSTD system response does not exceed 150 milliseconds. This test shall measure all the delay encountered by a step signal migrating from the pilot's control through the control loading electronics and interfacing through all the simulation software modules in the correct order, using a handshaking protocol, finally through the normal output interfaces to the motion system, to the visual system and instrument displays.</p> <p>(see next page)</p>											

SECTION 1

Appendix 1 to JAR-FSTD A.030 (continued)

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL	FTD LEVEL	FNPT LEVEL	BITD	COMPLIANCE							
					A	B	C	D	1	2	-	II
1.1 General												
(continued)												
	(2) Latency.	The visual system, flight deck instruments and initial motion system response shall respond to abrupt pitch, roll and yaw inputs from the pilot's position within 150 milliseconds of the time, but not before the time, when the aeroplane would respond under the same conditions.										

JAR-FSTD A

Appendix 1 to JAR-FSTD A.030 (continued)

SECTION 1

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS		FFS LEVEL			FTD LEVEL			FNPT LEVEL			BITD			COMPLIANCE		
		A	B	C	D	1	2	I	II	MCC						
s.1	Aerodynamic modelling shall be provided. This shall include, for aeroplanes issued an original type certificate after June 1980, low altitude level flight ground effect, Mach effect at high altitude, normal and reverse dynamic thrust effect on control surfaces, aerelastic representations, and representations of non-linearities due to sideslip based on aeroplane flight test data provided by the manufacturer.			✓	✓									Statement of Compliance required. Mach effect, aerelastic representations, and non-linearities due to sideslip are normally included in the FSTD aerodynamic model. The Statement of Compliance shall address each of these items. Separate tests for thrust effects and a Statement of Compliance are required.		
t.1	Modelling that includes the effects of airframe and engine icing.		✓	✓				✓	✓					Statement of Compliance required.		
u.1	Aerodynamic and ground reaction modelling for the effects of reverse thrust on directional control shall be provided.		✓	✓	✓									SOC shall describe the effects that provide training in the specific skills required for recognition of icing phenomena and execution of recovery.		
v.1	Realistic aeroplane mass properties, including mass, centre of gravity and moments of inertia as a function of payload and fuel loading shall be implemented.		✓	✓	✓	✓								Statement of Compliance required. (page 2-C-44).		
w.1	Self-testing for FSTD hardware and programming to determine compliance with the FSTD performance tests shall be provided. Evidence of testing shall include FSTD number, date, time, conditions, tolerances, and the appropriate dependent variables portrayed in comparison with the aeroplane standard.		✓	✓										Statement of Compliance required. Tests required.		

SECTION 1

Appendix 1 to JAR-FSTD A.030 (continued)

JAR-FSTD A

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL				FTD LEVEL		FNPT LEVEL		BITD		COMPLIANCE
	A	B	C	D	1	2	I	II	MCC		
x.1 Timely and permanent update of hardware and programming subsequent to aeroplane modification sufficient for the Qualification Level sought.	✓	✓	✓	✓	✓	✓					
y.1 Daily pre-flight documentation either in the daily log or in a location easily accessible for review is required.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	

2030

JAR-FSTD A

Appendix 1 to JAR-FSTD A.030 (continued)

SECTION 1

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL				FTD LEVEL			FNPT LEVEL			BITD	COMPLIANCE
	A	B	C	D	1	2	I	II	MCC			
2. Motion system												
a.1 Motion cues as perceived by the pilot shall be representative of the aeroplane, e.g. touchdown cues shall be a function of the simulated rate of descent.	✓	✓	✓	✓								For FSTDs where motion systems are not specifically required, but have been added, they will be assessed to ensure that they do not adversely affect the qualification of the FSTD.
b.1 A motion system shall:												Statement of Compliance required. Tests required.
(1) Provide sufficient cueing, which may be of a generic nature to accomplish the required tasks.	✓											
(2) Have a minimum of 3 degrees of freedom (pitch, roll & heave).					✓							
(3) Produce cues at least equivalent to those of a six-degrees-of-freedom synergistic platform motion system.						✓	✓					
c.1 A means of recording the motion response time as required.	✓	✓	✓	✓	✓	✓	✓	✓	✓			

SECTION 1

Appendix 1 to JAR-FSTD A.030 (continued)

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL	FTD LEVEL			FNPT LEVEL		BITD	COMPLIANCE
		A	B	C	D	1	2	
2. Motion system		✓	✓	✓	✓			
d.1 Motion effects programming shall include:								
(1) Effects of runway rumble, oleo deflections, groundspeed, uneven runway, centreline lights and taxiway characteristics.								
(2) Buffets on the ground due to spoiler/speedbrake extension and thrust reversal.								
(3) Bumps associated with the landing gear.								
(4) Buffet during extension and retraction of landing gear.								
(5) Buffet in the air due to flap and spoiler/speedbrake extension.								
(6) Approach to stall buffet.								
(7) Touchdown cues for main and nose gear.								
(8) Nose wheel scuffing.								
(9) Thrust effect with brakes set.								
								(See next page)

JAR-FSTD A

Appendix 1 to JAR-FSTD A.030 (continued)

SECTION 1

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL	FTD LEVEL				FNPT LEVEL			BITD	COMPLIANCE
		A	B	C	D	1	2	I	II	
d.1 (continued)	✓	✓	✓	✓						
(10) Mach and manoeuvre buffet.										
(11) Tyre failure dynamics.										
(12) Engine malfunction and engine damage.										
(13) Tail and pod strike.										
e.1 Motion vibrations: Tests with recorded results that allow the comparison of relative amplitudes versus frequency are required.					✓					Statement of Compliance required. Tests required.

SECTION 1

Appendix 1 to JAR-FSTD A.030 (continued)

	FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FS LEVEL				FTD LEVEL		FNPT LEVEL		BITD		COMPLIANCE
		A	B	C	D	1	2	I	II	MCC		
	3 Visual System											
a.1	The visual system shall meet all the standards enumerated as applicable to the level of qualification requested by the applicant.	✓	✓	✓	✓			✓	✓			For FTDs, FNPT 1s and BITDs, when visual systems have been added by the FSTD operator even though not attracting specific credits, they will be assessed to ensure that they do not adversely affect the qualification of the FSTD. For FTDs if the visual system is to be used for the training of manoeuvring by visual reference (such as route and airfield competence) then the visual system should at least comply with that required for level A FFS.
b.1	Continuous minimum collimated visual field-of-view of 45 degrees horizontal and 30 degrees vertical field of view simultaneously for each pilot.											SOC is acceptable in place of this test.
b.2	Continuous, cross-cockpit, minimum collimated visual field of view providing each pilot with 180 degrees horizontal and 40 degrees vertical field of view. Application of tolerances require the field of view to be not less than a total of 176 measured degrees horizontal field of view (including not less than ± 88 measured degrees either side of the centre of the design eye point) and not less than a total of 36 measured degrees vertical field of view from the pilot's and co-pilot's eye points.											Consideration shall be given to optimising the vertical field of view for the respective aeroplane cut-off angle. SOC is acceptable in place of this test.

JAR-FSTD A

Appendix 1 to JAR-FSTD A.030 (continued)

SECTION 1

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FS LEVEL				FTD LEVEL		FNPT LEVEL		BITD	COMPLIANCE
	A	B	C	D	1	2	I	II		
3 Visual System							✓	✓		
b.3 A visual system (night/dusk or day) capable of providing a field-of-view of a minimum of 45 degrees horizontally and 30 degrees vertically, unless restricted by the type of aeroplane, simultaneously for each pilot, including adjustable cloud base and visibility.										The visual system need not be collimated but shall be capable of meeting the standards laid down in Part 3 and 4 (Validation, Functions and Subjective Tests - See ACJ No.1 to JAR-FSTD A.030). SOC is acceptable in place of this test.
c.1 A means of recording the visual response time for visual systems.	✓	✓	✓	✓			✓	✓		
d.1 System Geometry. The system fitted shall be free from optical discontinuities and artefacts that create non-realistic cues.	✓	✓	✓	✓			✓	✓		Test required. A Statement of Compliance is acceptable in place of this test.
e.1 Visual textural cues to assess sink rate and depth perception during take-off and landing shall be provided.	✓	✓	✓	✓						For Level 'A' FFS visual cueing shall be sufficient to support changes in approach path by using runway perspective.
f.1 Horizon, and attitude shall correlate to the simulated attitude indicator.	✓	✓	✓	✓						Statement of Compliance required.
g.1 Occulting - A minimum of ten levels shall be available.	✓	✓	✓	✓						Occulting shall be demonstrated.
										Statement of Compliance required.
h.1 Surface (Vernier) resolution shall occupy a visual angle of not greater than 2 arc minutes in the visual display used on a scene from the pilot's eye-point.					✓	✓				Test and Statement of Compliance required containing calculations confirming resolution.

SECTION 1

Appendix 1 to JAR-FSTD A.030 (continued)

JAR-FSTD A

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FS LEVEL				FTD LEVEL		FNPT LEVEL		BITD		COMPLIANCE
	A	B	C	D	1	2	I	II	MCC		
3 Visual System											
i.1 Surface contrast ratio shall be demonstrated by a raster drawn test pattern showing a contrast ratio of not less than 5:1		✓	✓								Test and Statement of Compliance required.
j.1 Highlight brightness shall be demonstrated using a raster drawn test pattern. The highlight brightness shall not be less than 20 cd/m ² (6ft-lamberts).		✓	✓								Test and Statement of Compliance required. Use of calligraphic lights to enhance raster brightness is acceptable.
k.1 Light point size – not greater than 5 arc minutes.		✓	✓								Test and Statement of Compliance required. This is equivalent to a light point resolution of 2.5 arc minutes.
l.1 Light point contrast ratio – not less than 10:1	✓	✓									Test and Statement of compliance required.
l.2 Light point contrast ratio – not less than 25:1.		✓	✓								Test and Statement of compliance required.
m.1 Daylight, twilight and night visual capability as applicable for level of qualification sought.	✓	✓	✓	✓							Statement of Compliance required for system capability. System objective and scene content tests are required.
m.2 The visual system shall be capable of meeting, as a minimum, the system brightness and contrast ratio criteria as applicable for level of qualification sought	✓	✓	✓	✓							

JAR-FSTD A

Appendix 1 to JAR-FSTD A.030 (continued)

SECTION 1

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FS LEVEL				FTD LEVEL			FNPT LEVEL			BITD	COMPLIANCE
	A	B	C	D	1	2	I	II	MCC			
3 Visual System												
m.3 Total scene content shall be comparable in detail to that produced by 10000 visible textured surfaces and (in day) 6000 visible lights or (in twilight or night) 15000 visible lights, and sufficient system capacity to display 16 simultaneously moving objects.		✓	✓									
m.4 The system, when used in training, shall provide in daylight, full colour presentations and sufficient surfaces with appropriate textural cues to conduct a visual approach, landing and airport movement (taxi). Surface shading effects shall be consistent with simulated (static) sun position.		✓	✓									

SECTION 1

Appendix 1 to JAR-FSTD A.030 (continued)

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FS LEVEL				FTD LEVEL		FNPT LEVEL		BITD		COMPLIANCE
	A	B	C	D	1	2	I	II	MCC		
3 Visual System											
m.5 The system, when used in training, shall provide at twilight, as a minimum, full colour presentations of reduced ambient surfaces with sufficient intensity, appropriate textural cues that include self-illuminated objects such as road networks, ramp lighting and airport signage, to conduct a visual approach, landing and airport movement (taxi). Scenes shall include a definable horizon and typical terrain characteristics such as fields, roads and bodies of water and surfaces illuminated by representative ownership lighting (e.g. landing lights). If provided, directional horizon lighting shall have correct orientation and be consistent with surface shading effects.	✓	✓									
m.6 The system, when used in training, shall provide at night, as a minimum, all features applicable to the twilight scene, as defined above, with the exception of the need to portray reduced ambient intensity that removes ground cues that are not self-illuminating or illuminated by ownership lights (e.g. landing lights).	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	

JAR-FSTD A

Appendix 1 to JAR-FSTD A.030 (continued)

SECTION 1

FLIGHT SIMULATOR TRAINING DEVICE STANDARDS	FFS LEVEL				FTD LEVEL				FNPT LEVEL				BITD				COMPLIANCE
	A	B	C	D	1	2	I	II	MCC								
4 Sound System																	
a.1 Significant flight deck sounds which result from pilot actions corresponding to those of the aeroplane or class of aeroplane.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	For FNPT Level I and BITD engine sounds only need be available
b.1 Sound of precipitation, rain removal equipment and other significant aeroplane noises perceptible to the pilot during normal and abnormal operations and the sound of a crash when the FSTD is landed in excess of limitations.	✓	✓															Statement of Compliance required.
c.1 Comparable amplitude and frequency of flight deck noises, including engine and airframe sounds. The sounds shall be co-ordinated with the required weather.					✓												Tests required.
d.1 The volume control shall have an indication of sound level setting which meets all qualification requirements.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	

2039

Annexe II

Code JAR-FSTD (H) – Entraîneurs synthétiques de vol pour hélicoptères

Joint Aviation Requirements

JAR-FSTD H Helicopter Flight Simulation Training Devices

Initial issue
01 May 2008

All rights reserved

The members of the Joint Aviation Authorities Committee are representatives of the Civil Aviation Authorities of the countries that have signed the 'Arrangements Concerning the Development and the Acceptance of Joint Aviation Requirements'. A list of these countries is kept by European Civil Aviation Conference, 3 bis Villa Emile Bergerat, 92522 NEUILLY SUR SEINE Cedex, France.*

Further copies of the Joint Aviation Requirements can be purchased from IHS, Inc. , whose world-wide offices are listed on the JAA website (www.jaa.nl) and IHS website (www.global.ihs.com).

For electronic versions of Joint Aviation Authorities Documents please refer to the website of IHS, Inc. on www.ihs.com, where you will find information on how to order.

Enquiries regarding the contents should be addressed to the JAA, Saturnusstraat 40-44, PO Box 3000, 2130 KA HOOFDORP, The Netherlands (publications@jaat.eu).

*These countries are:

Albania, Armenia, Austria, [Azerbaijan], Belgium, Bosnia and Herzegovina, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, European Aviation Safety Agency, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Monaco, Netherlands, Norway, Poland, Portugal, Republic of Moldova, [Republic of Georgia], Romania, Serbia, Slovak Republic, Slovenia, Spain, Sweden, Switzerland, Turkey, Ukraine, & United Kingdom

CONTENTS (general layout)

JAR-FSTD H

HELICOPTER FLIGHT SIMULATION TRAINING DEVICES

FOREWORD

CHECK LIST OF PAGES

PREAMBLE

SECTION 1 – REQUIREMENTS

SUBPART A	—	APPLICABILITY
SUBPART B	—	GENERAL
SUBPART C	—	HELICOPTER FLIGHT SIMULATION TRAINING DEVICES

SECTION 2 – ADVISORY CIRCULARS JOINT (ACJ)

ACJ B	—	GENERAL
ACJ C	—	HELICOPTER FLIGHT SIMULATION TRAINING DEVICES

2042

JAR-FSTD H

INTENTIONALLY LEFT BLANK

CONTENTS (details)**JAR-FSTD H****HELICOPTER FLIGHT SIMULATION TRAINING DEVICES**

<i>Paragraph</i>		<i>Page</i>
SECTION 1 – REQUIREMENTS		
General and Presentation		1-0-1
SUBPART A – APPLICABILITY		
JAR-FSTD H.001	Applicability	1-A-1
SUBPART B – GENERAL		
JAR-FSTD H.005	Terminology	1-B-1
SUBPART C – HELICOPTER FLIGHT SIMULATION TRAINING DEVICES		
JAR-FSTD H.015	Application for FSTD Qualification	1-C-1
JAR-FSTD H.020	Validity FSTD Qualification	1-C-1
JAR-FSTD H.025	Rules governing FSTD Operators	1-C-1
JAR-FSTD H.030	Requirements for FSTDs qualified on or after 1 August 2008	1-C-2
JAR-FSTD H.031	Requirements for FFS qualified on or after 1 April 2001 and before 1 August 2008	1-C-2
JAR-FSTD H.032	Requirements for FTDs qualified on or after 1 January 2004 and before 1 August 2008	1-C-3
JAR-FSTD H.033	Requirements for FNPTs qualified on or after 1 January 2003 and before 1 August 2008	1-C-3
JAR-FSTD H.035	Requirements for FFSs approved or qualified before 1 April 2001	1-C-3
JAR-FSTD H.036	Requirements for FTDs approved or qualified before 1 January 2004	1-C-3
JAR-FSTD H.037	Requirements for FNPTs approved or qualified before 1 January 2003	1-C-4
JAR-FSTD H.040	Changes to qualified FSTDs	1-C-4
JAR-FSTD H.045	Interim FSTD Qualification	1-C-5
JAR-FSTD H.050	Transferability of FSTD Qualification	1-C-5
Appendix 1 to JAR-FSTD H.030	FSTD Standards	1-C-6

JAR-FSTD H

<i>Paragraph</i>	<i>Page</i>
SECTION 2 – ADVISORY CIRCULARS JOINT (ACJ)	
General and Presentation	2-0-1
ACJ B – GENERAL	
ACJ FSTD H.005	Terminology, Abbreviations
	2-B-1
ACJ C – HELICOPTER FLIGHT SIMULATION TRAINING DEVICES	
ACJ No. 1 to JAR-FSTD H.015	FSTD Qualification – Application and Inspection
ACJ No. 2 to JAR-FSTD H.015	FSTD Evaluations
ACJ to JAR-FSTD H.020	Validity of FSTD Qualification
ACJ No. 1 to JAR-FSTD H.025	Quality System
ACJ No. 2 to JAR-FSTD H.025	Installations
ACJ No. 1 to JAR-FSTD H.030	FSTDs qualified on or after 1 August 2008
Appendix 1 to ACJ No. 1 to JAR-FSTD H.030	Validation Test Tolerances
Appendix 2 to ACJ No. 1 to JAR-FSTD H.030	Validation Data Roadmap
Appendix 3 to ACJ No. 1 to JAR-FSTD H.030	Rotor Aerodynamic Modeling Techniques
Appendix 4 to ACJ No. 1 to JAR-FSTD H.030	Vibration Platforms for Helicopter FSTDs
Appendix 5 to ACJ No. 1 to JAR-FSTD H.030	Transport Delay Testing Method
Appendix 6 to ACJ No. 1 to JAR-FSTD H.030	Recurrent Evaluations – Validation Test Data Presentation
Appendix 7 to ACJ No 1 to JAR-FSTD H.030	Applicability
Appendix 8 to ACJ No 1 JAR-FSTD H.030	Visual Display Systems
Appendix 9 to ACJ No 1 JAR-FSTD H.030	General technical Requirements for FSTD Qualification Levels
ACJ No. 2 to JAR-FSTD H.030	Guidance on Design & Qualification of Level 'A' Helicopter FFS
ACJ No. 3 to JAR-FSTD H.030	Guidance on Design & Qualification of Helicopter FTDs
ACJ No. 4 to JAR-FSTD H.030	Use of Data for Helicopter FTDs
ACJ No. 5 to JAR-FSTD H.030	Guidance on Design & Qualification of Helicopter FNPTs
	2-C-122
	2-C-127
	2-C-129
	2-C-132
	2-C-133

JAR-FSTD H

<i>Paragraph</i>		<i>Page</i>
ACJ No. 1 to JAR-FSTD H.030(c)(1)	Engineering Simulator Validation Data	2-C-141
ACJ No. 2 to JAR-FSTD H.030(c)(1)	Engineering Simulator Validation Data – Approved Guidelines	2-C-142
ACJ to FSTD H.035	FFS Approved or Qualified before 1 April 2001	2-C-144
ACJ to FSTD H.037	FNPTs Approved or Qualified before 1 January 2003	2-C-145
ACJ to FSTD H.045	New Helicopter FFS/FTD Qualification	2-C-146

INTENTIONALLY LEFT BLANK

2046

JAR-FSTD H

INTENTIONALLY LEFT BLANK

FOREWORD

- 1 The Civil Aviation Authorities of certain European countries have agreed common comprehensive and detailed aviation requirements, referred to as Joint Aviation Requirements (JARs), with a view to minimising Type Certification problems on joint ventures, to facilitate the export and import of aviation products, to make it easier for maintenance carried out in one European country to be accepted by the Civil Aviation Authority in another European country and to regulate commercial air transport operations.
- 2 JARs are recognised by the Civil Aviation Authorities of participating countries as an acceptable basis for showing compliance with their national codes.
- 3 The content has been prepared using the expertise available in this field and added to where necessary by making use of existing European regulations and the Federal Aviation Requirements of the United States of America where acceptable.
- 4 JAR-FSTD H is issued with no National Variants. It may be felt that the document does not contain all of the detailed compliance and interpretative information which some Civil Aviation Authorities and Industry organisations would like to see. However, it is accepted that JAR-FSTD H should be applied in practice and the lessons learned embodied in future amendments. The Civil Aviation Authorities of the JAA are therefore committed to early amendment in the light of experience.
- 5 Future development of the requirements of JAR-FSTD H, including the commitment in Paragraph 4, will be in accordance with the JAA's Notice of Proposed Amendment (NPA) procedures. These procedures allow for the amendment of JAR-FSTD H to be proposed by any organisation or person.
- 6 The Civil Aviation Authorities have agreed they should not unilaterally initiate amendment of their national codes without having made a proposal for amendment of JAR-FSTD H in accordance with the agreed procedure.
- 7 Definitions and abbreviations of terms used in JAR-FSTD H that are considered generally applicable are contained in JAR-1, Definitions and Abbreviations. However, definitions and abbreviations of terms used in JAR-FSTD H that are specific to a Subpart of JAR-FSTD H are normally given in the Subpart concerned or, exceptionally, in the associated compliance or interpretative material.
- 8 Amendments to the text in JAR-FSTD H are issued as Replacement Pages. These show an effective date and have the same status and applicability as JAR-FSTD H from that date.
- 9 New, amended and corrected text will be enclosed within heavy brackets until a subsequent 'Amendment' is issued.
- 10 Comment/Response documents developed following Notices of Proposed Amendment (NPA) consultation have been produced by the JAA and are published on the JAA Internet Site: www.jaa.nl. Readers can also apply to Central JAA for copies of specific Comment/Response Documents as required.

2048

JAR-FSTD H

INTENTIONALLY LEFT BLANK

JOINT AVIATION REQUIREMENTS

CHECK LIST OF PAGES

JAR-FSTD H - HELICOPTER FLIGHT SIMULATION TRAINING DEVICES

Initial issue dated 01 May 2008

The following pages of JAR-FSTD H are now current:

<i>Page No</i>	<i>Legend</i>	<i>Date</i>
Title Page	Initial issue	01.05.08
ii	Initial issue	01.05.08
C-1	Initial Issue	01.05.08
C-2	Initial Issue	01.05.08
C-3	Initial Issue	01.05.08
C-4	Initial Issue	01.05.08
C-5	Initial Issue	01.05.08
C-6	Initial Issue	01.05.08
F-1	Initial Issue	01.05.08
F-2	Initial Issue	01.05.08
CL-1	Initial Issue	01.05.08
CL-2	Initial Issue	01.05.08
CL-3	Initial Issue	01.05.08
CL-4	Initial Issue	01.05.08
P-1	Initial Issue	01.05.08
P-2	Initial Issue	01.05.08
1-0-1	Initial Issue	01.05.08
1-0-2	Initial Issue	01.05.08
1-A-1	Initial Issue	01.05.08
1-A-2	Initial Issue	01.05.08
1-B-1	Initial Issue	01.05.08
1-B-2	Initial Issue	01.05.08
1-C-1	Initial Issue	01.05.08
1-C-2	Initial Issue	01.05.08
1-C-3	Initial Issue	01.05.08
1-C-4	Initial Issue	01.05.08
1-C-5	Initial Issue	01.05.08
1-C-6	Initial Issue	01.05.08
1-C-7	Initial Issue	01.05.08
1-C-8	Initial Issue	01.05.08
1-C-9	Initial Issue	01.05.08
1-C-10	Initial Issue	01.05.08
1-C-11	Initial Issue	01.05.08
1-C-12	Initial Issue	01.05.08
1-C-13	Initial Issue	01.05.08
1-C-14	Initial Issue	01.05.08
1-C-15	Initial Issue	01.05.08
1-C-16	Initial Issue	01.05.08
1-C-17	Initial Issue	01.05.08
1-C-18	Initial Issue	01.05.08

JAR-FSTD H

<i>Paragraph</i>	<i>Legend</i>	<i>Page</i>
1-C-19	Initial Issue	01.05.08
1-C-20	Initial Issue	01.05.08
1-C-21	Initial Issue	01.05.08
1-C-22	Initial Issue	01.05.08
1-C-23	Initial Issue	01.05.08
1-C-24	Initial Issue	01.05.08
1-C-25	Initial Issue	01.05.08
1-C-26	Initial Issue	01.05.08
1-C-27	Initial Issue	01.05.08
1-C-28	Initial Issue	01.05.08
2-0-1	Initial Issue	01.05.08
2-0-2	Initial Issue	01.05.08
2-B-1	Initial Issue	01.05.08
2-B-2	Initial Issue	01.05.08
2-B-3	Initial Issue	01.05.08
2-B-4	Initial Issue	01.05.08
2-B-5	Initial Issue	01.05.08
2-B-6	Initial Issue	01.05.08
2-B-7	Initial Issue	01.05.08
2-B-8	Initial Issue	01.05.08
2-C-1	Initial Issue	01.05.08
2-C-2	Initial Issue	01.05.08
2-C-3	Initial Issue	01.05.08
2-C-4	Initial Issue	01.05.08
2-C-5	Initial Issue	01.05.08
2-C-6	Initial Issue	01.05.08
2-C-7	Initial Issue	01.05.08
2-C-8	Initial Issue	01.05.08
2-C-9	Initial Issue	01.05.08
2-C-10	Initial Issue	01.05.08
2-C-11	Initial Issue	01.05.08
2-C-12	Initial Issue	01.05.08
2-C-13	Initial Issue	01.05.08
2-C-14	Initial Issue	01.05.08
2-C-15	Initial Issue	01.05.08
2-C-16	Initial Issue	01.05.08
2-C-17	Initial Issue	01.05.08
2-C-18	Initial Issue	01.05.08
2-C-19	Initial Issue	01.05.08
2-C-20	Initial Issue	01.05.08
2-C-21	Initial Issue	01.05.08
2-C-22	Initial Issue	01.05.08
2-C-23	Initial Issue	01.05.08
2-C-24	Initial Issue	01.05.08
2-C-25	Initial Issue	01.05.08
2-C-26	Initial Issue	01.05.08
2-C-27	Initial Issue	01.05.08
2-C-28	Initial Issue	01.05.08
2-C-29	Initial Issue	01.05.08
2-C-30	Initial Issue	01.05.08
2-C-31	Initial Issue	01.05.08
2-C-32	Initial Issue	01.05.08
2-C-33	Initial Issue	01.05.08
2-C-34	Initial Issue	01.05.08
2-C-35	Initial Issue	01.05.08
2-C-36	Initial Issue	01.05.08
2-C-37	Initial Issue	01.05.08
2-C-38	Initial Issue	01.05.08
2-C-39	Initial Issue	01.05.08
2-C-40	Initial Issue	01.05.08

<i>Paragraph</i>	<i>Legend</i>	<i>Page</i>
2-C-41	Initial Issue	01.05.08
2-C-42	Initial Issue	01.05.08
2-C-43	Initial Issue	01.05.08
2-C-44	Initial Issue	01.05.08
2-C-45	Initial Issue	01.05.08
2-C-46	Initial Issue	01.05.08
2-C-47	Initial Issue	01.05.08
2-C-48	Initial Issue	01.05.08
2-C-49	Initial Issue	01.05.08
2-C-50	Initial Issue	01.05.08
2-C-51	Initial Issue	01.05.08
2-C-52	Initial Issue	01.05.08
2-C-53	Initial Issue	01.05.08
2-C-54	Initial Issue	01.05.08
2-C-55	Initial Issue	01.05.08
2-C-56	Initial Issue	01.05.08
2-C-57	Initial Issue	01.05.08
2-C-58	Initial Issue	01.05.08
2-C-59	Initial Issue	01.05.08
2-C-60	Initial Issue	01.05.08
2-C-61	Initial Issue	01.05.08
2-C-62	Initial Issue	01.05.08
2-C-63	Initial Issue	01.05.08
2-C-64	Initial Issue	01.05.08
2-C-65	Initial Issue	01.05.08
2-C-66	Initial Issue	01.05.08
2-C-67	Initial Issue	01.05.08
2-C-68	Initial Issue	01.05.08
2-C-69	Initial Issue	01.05.08
2-C-70	Initial Issue	01.05.08
2-C-71	Initial Issue	01.05.08
2-C-72	Initial Issue	01.05.08
2-C-73	Initial Issue	01.05.08
2-C-74	Initial Issue	01.05.08
2-C-75	Initial Issue	01.05.08
2-C-76	Initial Issue	01.05.08
2-C-77	Initial Issue	01.05.08
2-C-78	Initial Issue	01.05.08
2-C-79	Initial Issue	01.05.08
2-C-80	Initial Issue	01.05.08
2-C-81	Initial Issue	01.05.08
2-C-82	Initial Issue	01.05.08
2-C-83	Initial Issue	01.05.08
2-C-84	Initial Issue	01.05.08
2-C-85	Initial Issue	01.05.08
2-C-86	Initial Issue	01.05.08
2-C-87	Initial Issue	01.05.08
2-C-88	Initial Issue	01.05.08
2-C-89	Initial Issue	01.05.08
2-C-90	Initial Issue	01.05.08
2-C-91	Initial Issue	01.05.08
2-C-92	Initial Issue	01.05.08
2-C-93	Initial Issue	01.05.08
2-C-94	Initial Issue	01.05.08
2-C-95	Initial Issue	01.05.08
2-C-96	Initial Issue	01.05.08
2-C-97	Initial Issue	01.05.08
2-C-98	Initial Issue	01.05.08
2-C-99	Initial Issue	01.05.08
2-C-100	Initial Issue	01.05.08
2-C-101	Initial Issue	01.05.08
2-C-102	Initial Issue	01.05.08
2-C-103	Initial Issue	01.05.08

JAR-FSTD H

<i>Paragraph</i>	<i>Legend</i>	<i>Page</i>
2-C-104	Initial Issue	01.05.08
2-C-105	Initial Issue	01.05.08
2-C-106	Initial Issue	01.05.08
2-C-107	Initial Issue	01.05.08
2-C-108	Initial Issue	01.05.08
2-C-109	Initial Issue	01.05.08
2-C-110	Initial Issue	01.05.08
2-C-111	Initial Issue	01.05.08
2-C-112	Initial Issue	01.05.08
2-C-113	Initial Issue	01.05.08
2-C-114	Initial Issue	01.05.08
2-C-115	Initial Issue	01.05.08
2-C-116	Initial Issue	01.05.08
2-C-117	Initial Issue	01.05.08
2-C-118	Initial Issue	01.05.08
2-C-119	Initial Issue	01.05.08
2-C-120	Initial Issue	01.05.08
2-C-121	Initial Issue	01.05.08
2-C-122	Initial Issue	01.05.08
2-C-123	Initial Issue	01.05.08
2-C-124	Initial Issue	01.05.08
2-C-125	Initial Issue	01.05.08
2-C-126	Initial Issue	01.05.08
2-C-127	Initial Issue	01.05.08
2-C-128	Initial Issue	01.05.08
2-C-129	Initial Issue	01.05.08
2-C-130	Initial Issue	01.05.08
2-C-131	Initial Issue	01.05.08
2-C-132	Initial Issue	01.05.08
2-C-133	Initial Issue	01.05.08
2-C-134	Initial Issue	01.05.08
2-C-135	Initial Issue	01.05.08
2-C-136	Initial Issue	01.05.08
2-C-137	Initial Issue	01.05.08
2-C-138	Initial Issue	01.05.08
2-C-139	Initial Issue	01.05.08
2-C-140	Initial Issue	01.05.08
2-C-141	Initial Issue	01.05.08
2-C-142	Initial Issue	01.05.08
2-C-143	Initial Issue	01.05.08
2-C-144	Initial Issue	01.05.08
2-C-145	Initial Issue	01.05.08
2-C-146	Initial Issue	01.05.08
2-C-147	Initial Issue	01.05.08
2-C-148	Initial Issue	01.05.08

PREAMBLE

JAR-FSTD H

Initial Issue

JAR-FSTD H comprises 3 Subparts (A, B and C) in Section 1, and 2 Subparts (B and C) in Section 2.

JAR-FSTD H is a simple amalgamation of JAR STD 1H, 2H and 3H into one document.

Section 1

Subpart A

Applicability to all Helicopter FSTD

Subpart B

Terminology for all Helicopter FSTD and implementation

Subpart C

Basic regulatory processes

Table of Standards in Appendix 1 to JAR-FSTD H.030 contains the standard for all devices

Section 2

Subpart B

Terminology and Abbreviations rationalised and harmonised with Helicopter STD standards documents.

Subpart C

Regulatory Processes combined.

Table of Objective Tests (ACJ No. 1 to JAR-FSTD H.030) contains the testing requirements for all devices.

Table of Functions and Subjective Tests (ACJ No. 1 to JAR-FSTD H.030) contains the testing requirements for all devices

2054

JAR-FSTD H

INTENTIONALLY LEFT BLANK

SECTION 1**JAR-FSTD H****SECTION 1 – REQUIREMENTS****1 GENERAL**

1.1 This Section contains the requirements for helicopter Flight Simulation Training Devices.

2 PRESENTATION

2.1 The requirements of JAR–FSTD H are presented in two columns on loose pages, each page being identified by the date of issue and the Amendment number under which it is amended or reissued.

2.2 Sub-headings are in italic typeface.

2.3 Explanatory Notes not forming part of the requirements appear in smaller typeface.

2.4 New, amended and corrected text will be enclosed within heavy brackets until a subsequent 'Amendment' is issued.

2.5 After each paragraph, the various changes and amendments, if any since the initial issue, are indicated together with their date of issue.

INTENTIONALLY LEFT BLANK

2056

JAR-FSTD H

SECTION 1

INTENTIONALLY LEFT BLANK

SECTION 1**JAR-FSTD H****SUBPART A - APPLICABILITY****JAR-FSTD H.001 Applicability**

JAR-FSTD H as amended applies to those persons, organisations or enterprises (Flight Simulation Training Devices (FSTD) operators) seeking initial qualification of FSTDs.

The version of JAR-FSTD H agreed by the Authority and used for issue of the initial qualification shall be applicable for future recurrent qualifications of the FSTD unless recategorised.

FSTD users shall also gain approval to use the FSTD as part of their approved training programmes despite the fact that the FSTD has been previously qualified.

INTENTIONALLY LEFT BLANK

INTENTIONALLY LEFT BLANK

2058

JAR-FSTD H

SECTION 1

INTENTIONALLY LEFT BLANK

SECTION 1**JAR-FSTD H****SUBPART B – GENERAL****JAR-FSTD H.005(f) (continued)****JAR-FSTD H.005 Terminology**

(See ACJ to FSTD H.005)

Because of the technical complexity of FSTD qualification, it is essential that standard terminology is used throughout. The following principal terms and abbreviations shall be used in order to comply with JAR-FSTD (H). Further terms and abbreviations are contained in ACJ to FSTD H.005.

(a) *Flight Simulation Training Device (FSTD)*. A training device which is a Full Flight Simulator (FFS), a Flight Training Device (FTD), a Flight & Navigation Procedures Trainer (FNPT).

(b) *Full Flight Simulator (FFS)*. A full size replica of a specific type or make, model and series helicopter flight deck, including the assemblage of all equipment and computer programmes necessary to represent the helicopter in ground and flight operations, a visual system providing an out of the flight deck view, and a force cueing motion system. It is in compliance with the minimum standards for FFS Qualification.

(c) *Flight Training Device (FTD)*. A full size replica of a specific helicopter type's instruments, equipment, panels and controls in an open flight deck area or an enclosed helicopter flight deck, including the assemblage of equipment and computer software programmes necessary to represent the helicopter in ground and flight conditions to the extent of the systems installed in the device. It does not require a force cueing motion or visual system. It is in compliance with the minimum standards for a specific FTD Level of Qualification.

(d) *Flight and Navigation Procedures Trainer (FNPT)*. A training device which represents the flight deck or cockpit environment including the assemblage of equipment and computer programmes necessary to represent a helicopter in flight operations to the extent that the systems appear to function as in a helicopter. It is in compliance with the minimum standards for a specific FNPT Level of Qualification.

(e) *Other Training Device (OTD)*. A training aid other than FFS, FTD or FNPT which provides for training where a complete flight deck environment is not necessary.

(f) *Flight Simulation Training Device User Approval (FSTD User Approval)*. The extent to which an FSTD of a specified Qualification Level may be used by persons, organisations or enterprises as approved by the Authority. It takes

account of helicopter to FSTD differences and the operating and training ability of the organization.

(g) *Flight Simulation Training Device Operator (FSTD operator)*. That person, organisation or enterprise directly responsible to the Authority for requesting and maintaining the qualification of a particular FSTD.

(h) *Flight Simulation Training Device User (FSTD User)*. The person, organization or enterprise requesting training, checking and testing credits through the use of an FSTD.

(i) *Flight Simulation Training Device Qualification (FSTD Qualification)*. The level of technical ability of an FSTD as defined in the compliance document.

(j) *Qualification Test Guide (QTG)*. A document designed to demonstrate that the performance and handling qualities of an FSTD agree within prescribed limits with those of the helicopter and that all applicable regulatory requirements have been met. The QTG includes both the helicopter and FSTD data used to support the validation.

INTENTIONALLY LEFT BLANK

2060

JAR-FSTD H

SECTION 1

INTENTIONALLY LEFT BLANK

SECTION 1**SUBPART C – HELICOPTER FLIGHT SIMULATION TRAINING DEVICES**

JAR-FSTD H.015 Application for FSTD Qualification
 (See ACJ No. 1 to JAR-FSTD H.015)
 (See ACJ No. 2 to JAR-FSTD H.015)

(a) The FSTD operator requiring evaluation of a FFS, FTD, or FNPT shall apply to the Authority giving 3 months notice. In exceptional cases this period may be reduced to one month at the discretion of the Authority.

(b) An FSTD Qualification Certificate will be issued following satisfactory completion of an evaluation of the FFS, FTD or FNPT by the Authority.

JAR-FSTD H.020 Validity of FSTD Qualification
 (See ACJ to JAR-FSTD H.020)

(a) A FSTD qualification is valid for 12 months unless otherwise specified by the Authority.

(b) A FSTD qualification revalidation can take place at any time within the 60 days prior to the expiry of the validity of the qualification document. The new period of validity shall continue from the expiry date of the previous qualification document.

(c) The Authority shall refuse, revoke, suspend or vary a FSTD qualification, if the provisions of JAR-FSTD H are not satisfied.

JAR-FSTD H.025 Rules Governing FSTD Operators
 (See ACJ No. 1 to JAR-FSTD H.025)
 (See ACJ No. 2 to JAR-FSTD H.025)

The FSTD operator shall demonstrate his capability to maintain the performance, functions and other characteristics specified for the FSTD Qualification Level as follows:

(a) Quality System

(1) A Quality System shall be established and a Quality Manager designated to monitor compliance with, and the adequacy of, procedures required to ensure the maintenance of the Qualification Level of

JAR-FSTD H.025(a) (continued)

FSTDs. Compliance monitoring shall include a feedback system to the Accountable Manager to ensure corrective action as necessary.

(2) The Quality System shall include a Quality Assurance Programme that contains procedures designed to verify that the specified performance, functions and characteristics are being conducted in accordance with all applicable requirements, standards and procedures.

(3) The Quality System and the Quality Manager shall be acceptable to the Authority.

(4) The Quality System shall be described in relevant documentation.

(b) Updating. A link shall be maintained between the operator's organization, the Authority and the relevant manufacturers to incorporate important modifications, especially:

(1) Helicopter modifications which are essential for training and checking shall be introduced into all affected FSTDs whether or not enforced by an airworthiness directive.

(2) Modification of FSTDs, including motion and visual systems (where applicable):

(i) When essential for training and checking, FSTD operators shall update their FSTDs (for example in the light of data revisions). Modifications of the FSTD hardware and software which affect handling, performance and systems operation or any major modifications of the motion or visual system shall be evaluated to determine the impact on the original qualification criteria. FSTD operators shall prepare amendments for any affected validation tests. The FSTD operator shall test the FSTD to the new criteria.

(ii) The Authority shall be advised in advance of any major changes to determine if the tests carried out by the FSTD operator are satisfactory. A special evaluation of the FSTD may be necessary prior to returning it to training following the modification.

(c) Installations. Ensure that the FSTD is housed in a suitable environment which supports safe and reliable operation.

JAR-FSTD H

JAR-FSTD H.025(c) (continued)

(1) The FSTD operator shall ensure that the FSTD and its installation comply with the local regulations for health and safety. However, as a minimum all FSTD occupants and maintenance personnel shall be briefed on FSTD safety to ensure that they are aware of all safety equipment and procedures in the FSTD in case of emergency.

(2) The FSTD safety features such as emergency stops and emergency lighting shall be checked at least annually and recorded by the FSTD operator.

(d) Additional Equipment. Where additional equipment has been added to the FSTD even though not required for qualification, it will be assessed to ensure that it does not adversely affect the quality of training. Therefore any subsequent modification, removal or unserviceability of such equipment could affect the qualification of the device.

JAR-FSTD H.030 Requirements for FSTD qualified on or after 1 August 2008

(See Appendix 1 to JAR-FSTD H.030)
 (See ACJ No. 1 to JAR-FSTD H.030)
 (See ACJ No. 2 to JAR-FSTD H.030)
 (See ACJ No. 3 to JAR-FSTD H.030)
 (See ACJ No. 4 to JAR-FSTD H.030)
 (See ACJ No. 5 to JAR-FSTD H.030)

(a) Any FSTD submitted for initial evaluation on or after 1 August 2008 will be evaluated against applicable JAR-FSTD H criteria for the Qualifications levels for which qualification has been applied. Recurrent evaluations of a FSTD will be based on the same version of JAR-FSTD H that was applicable for its initial evaluation. An upgrade will be based upon the currently applicable version of JAR-FSTD H.

(b) A FSTD shall be assessed in those areas which are essential to completing the flight crew member training, testing and checking process as applicable.

(c) The FSTD shall be subjected to:

(1) Validation tests and

SECTION 1

JAR-FSTD H.030(c) (continued)

(2) Functions & subjective tests

(d) Data shall be of a standard that satisfies the Authority before the FSTD can gain a Qualification Level.

(e) The FSTD operator shall submit a QTG in a form and manner which is acceptable to the Authority.

(f) The QTG will only be approved after completion of an initial or upgrade evaluation, and when all the discrepancies in the QTG have been addressed to the satisfaction of the Authority. After inclusion of the results of the tests witnessed by the Authority, the approved QTG becomes the Master QTG (MQTG), which is the basis for the FSTD qualification and subsequent recurrent FSTD evaluations

(g) The FSTD operator shall:

(1) Run the complete set of tests contained within the MQTG progressively between each annual evaluation by the Authority. Results shall be dated and retained in order to satisfy both the FSTD operator and the Authority that FSTD standards are being maintained; and

(2) Establish a Configuration Control System to ensure the continued integrity of the hardware and software of the qualified FSTD.

JAR-FSTD H.031 Requirements for FFS qualified on or after 1 April 2001 and before 1 August 2008

Any FFS submitted for initial evaluation on or after 1 April 2001 and before 1 August 2008, shall automatically be granted an equivalent qualification under JAR-FSTD H with effect from the re-evaluation conducted at the end of the current validity period. This re-evaluation, and all future re-evaluations, will be conducted in accordance with the requirements of the same version of JAR-STD 1H, which was applicable for its last evaluation prior to implementation of JAR-FSTD H. Any upgrade will be based on the currently applicable version of JAR-FSTD H.

SECTION 1

JAR-FSTD H.032 Requirements for Flight Training Devices (FTD) qualified on or after 1 January 2004 and before 1 August 2008

Any FTD submitted for initial evaluation on or after 1 January 2004 and before 1 August 2008, shall automatically be granted an equivalent qualification under JAR-FSTD H with effect from the re-evaluation conducted at the end of the current validity period. This re-evaluation, and all future re-evaluations, will be conducted in accordance with the requirements of the same version of JAR-STD 2H, which was applicable for its last evaluation prior to implementation of JAR-FSTD H. Any upgrade will be based on the currently applicable version of JAR-FSTD H.

JAR-FSTD H.033 Requirements for Flight & Navigation Procedures Trainers (FNPT) qualified on or after 1 January 2003 and before 1 August 2008

Any FNPT submitted for initial evaluation on or after 1 January 2003 and before 1 August 2008, shall automatically be granted an equivalent qualification under JAR-FSTD H with effect from the re-evaluation conducted at the end of the current validity period. This re-evaluation, and all future re-evaluations, will be conducted in accordance with the requirements of the same version of JAR-STD 3H, which was applicable for its last evaluation prior to implementation of JAR-FSTD H. Any upgrade will be based on the currently applicable version of JAR-FSTD H.

JAR-FSTD H.035 Requirements for Full Flight Simulators approved or qualified before 1 April 2001
 (See ACJ to JAR-FSTD H.035)

(a) FFS approved or qualified in accordance with national regulations of JAA Member States before 1 April 2001 will either be recategorised or will continue to maintain their approval under the Grandfather Rights provision, in accordance with sub-paragraphs (c) and (d) below. For FFS which are not recategorized, maximum credit shall under no

JAR-FSTD H

JAR-FSTD H.035(a) (continued)

circumstances exceed originally issued National credits.

(b) FFS's neither recategorised nor with an approval maintained under the Grandfather Rights provision, will be qualified in accordance with JAR-FSTD H.030.

(c) FFS that are not recategorised but that have a primary reference document used for their testing may be qualified by the Authority to an equivalent JAR-FSTD H Qualification Level, either AG, BG, CG or DG. An upgrade requires the recategorisation of the FFS.

(1) To gain and maintain an equivalent Qualification Level, these FFS shall be assessed in those areas which are essential to completing the flight crew member training and checking process, as applicable.

(2) The FFS shall be subjected to:

- (i) Validation tests; and
- (ii) Functions and subjective tests.

(d) FFS that are not recategorised and that do not have a primary reference document used for their testing, shall be qualified by special arrangement. Such FFS will be issued with a Special Category and shall be subjected to functions and subjective tests corresponding to those detailed within this document. In addition any previously recognised validation test shall be used.

JAR-FSTD H.036 Requirements for Flight Training Devices approved or qualified before 1 January 2004

No longer applicable.

INTENTIONALLY LEFT BLANK

JAR-FSTD H**SECTION 1**

JAR-FSTD H.037 Requirements for Flight Navigation Procedures Trainers approved or qualified before 1 January 2003
 (See ACJ to JAR-FSTD H.037)

(a) FNPTs or devices approved or qualified in accordance with national regulations of JAA Members States before 1 January 2003 will either be recategorised or will continue to maintain their approval under the Grandfather Rights provision, in accordance with sub-paragraphs (c) and (d) below. Grandfather Rights shall cease to exist on the 1st January 2009. For FNPT which are not recategorised maximum credits shall under no circumstances exceed originally issued National credits.

(b) Recategorised FNPTs will be qualified in accordance with JAR-FSTD H.030.

(c) FNPTs that are not recategorised, but that have a primary reference document used for their testing, may continue under previous authorisation, provided that they continue to comply with the primary reference document.

(1) To gain and maintain their equivalent qualification level, these FNPTs shall be assessed in those areas which are essential to completing the flight crew member training process, as applicable.

(2) The devices shall be subjected to:

- (i) Validation tests and
- (ii) Functions and subjective tests.

(d) FNPTs that are not recategorised and that do not have a primary reference document used for their testing shall be qualified by special arrangement. Such FNPTs will be issued with a Special Category and shall be subjected to Functions and Subjective Tests corresponding to those detailed within this document. In addition any previously recognized Validation tests shall be used.

JAR-FSTD H.040 Changes to qualified FSTD

(a) Requirement to notify major changes to a FSTD. The operator of a qualified FSTD shall inform the Authority of proposed major changes such as:

JAR-FSTD H.040(a) (continued)

(1) Helicopter modifications which could affect FSTD qualification.

(2) FSTD hardware and or software modifications which could affect the handling qualities, performance or system representations.

(3) Relocation of the FSTD; and

(4) Any deactivation of the FSTD.

The Authority may complete a special evaluation following major changes or when a FSTD appears not to be performing at its initial Qualification Level.

(b) Upgrade of a FSTD. A FSTD may be upgraded to a higher Qualification Level. Special evaluation is required before the award of a higher Level of Qualification.

(1) If an upgrade is proposed the FSTD operator shall seek the advice of the Authority and give full details of the modifications. If the upgrade evaluation does not fall upon the anniversary of the original qualification date, a special evaluation is required to permit the FSTD to continue to qualify even at the previous Qualification Level.

(2) In the case of a FSTD upgrade, an FSTD operator shall run all validation tests for the requested Qualification Level. Results from previous evaluations shall not be used to validate FSTD performance for the current upgrade.

(c) Relocation of a FSTD

(1) In instances where a FSTD is moved to a new location, the Authority shall be advised before the planned activity along with a schedule of related events.

(2) Prior to returning the FSTD to service at the new location the FSTD operator shall perform at least one third of the validation tests and all functions and subjective tests to ensure that the FSTD performance meets its original qualification standard. A copy of the test documentation shall be retained together with the FSTD records for review by the Authority.

(3) An evaluation of the FSTD in accordance with its original JAA qualification criteria shall be at the discretion of the Authority.

(d) Deactivation of a currently qualified FSTD

SECTION 1

JAR-FSTD H.040(d) (continued)

(1) If a FSTD operator plans to remove a FSTD from active status for prolonged periods, the Authority shall be notified and suitable controls established for the period during which the FSTD is inactive.

(2) The FSTD operator shall agree a procedure with the Authority to ensure that the FSTD can be restored to active status at its original Qualification Level.

JAR-FSTD H.045 Interim FSTD Qualification
(See ACJ to JAR-FSTD H.045)

(a) In the case of new helicopter programmes, special arrangements shall be made to enable an interim Qualification Level to be achieved.

(b) For Full Flight Simulators, an interim Qualification Level will only be granted at levels A, B or C

(c) Requirements, details relating to the issue, and the period of validity of an interim Qualification Level will be decided by the Authority.

INTENTIONALLY LEFT BLANK

JAR-FSTD H.050 Transferability of FSTD Qualification

When there is a change of FSTD operator:

(a) The new FSTD operator shall advise the Authority in advance in order to agree upon a plan of transfer of the FSTD.

(b) At the discretion of the Authority, the FSTD shall be subject to an evaluation in accordance with its original JAA qualification criteria.

(c) Provided that the FSTD performs to its original standard, its original Qualification Level shall be restored. Revised user approval(s) may also be required.

INTENTIONALLY LEFT BLANK

Appendix 1 to JAR-FSTD H.030**Flight Simulation Training Device Standards General**

This appendix describes the minimum Full Flight Simulator (FFS), Flight Training Device (FTD) and Flight Navigation Procedures Trainer (FNPT) requirements for qualifying devices to the required Qualification Levels. Certain requirements included in this section shall be supported with a statement of compliance (SOC) and, in some designated cases, an objective test. The SOC will describe how the requirement was met. The test results shall show that the requirement has been attained. In the following tabular listing of FSTD standards, statements of compliance are indicated in the compliance column.

For FNPT use in Multi-Crew Co-operation (MCC) training the general technical requirement are expressed in the MCC column with additional systems, instrumentation and indicators as required for MCC training and operation.

For MCC (Multi Crew Co-operation) minimum technical requirements are as for Level II or III, with the following additions or amendments:

1	Multi engine and multi pilot helicopter
2	Performance reserves, in case of an engine failure, to be in accordance with CAT. A criteria.
3	Anti icing or de-icing systems
4	Fire detection / suppression system
5	Dual controls
6	Autopilot with upper modes
7	2 VHF transceivers
8	2 VHF NAV receivers (VOR, ILS, DME)
9	1 ADF receiver
10	1 Marker receiver
11	1 transponder
12	Weather radar

The following indicators shall be located in the same positions on the instrument panels of both pilots:

1	Airspeed
2	Flight attitude
3	Altimeter and radio altimeter
4	HSI
5	Vertical speed
6	ADF
7	VOR, ILS, DME
8	Marker indication
9	Stop watch

SECTION 1

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS	FFS LEVEL				FTD LEVEL				FNPT LEVEL				COMPLIANCE
	A	B	C	D	1	2	3	I	II	III	MCC		
1.1 General													
a.1 A flight deck that is a full-scale replica of the helicopter simulated. Additional required crewmember duty stations and those required bulkheads aft of the pilot seats are also considered part of the cockpit and shall replicate the helicopter.	✓	✓	✓		✓	✓							
A flight deck that replicates the helicopter.					✓			✓	✓	✓	✓		
a.2 The flight deck, including the instructor's station is fully enclosed.	✓	✓	✓		✓			✓	✓	✓	✓		
A flight deck, including the instructor's station that is sufficiently closed off to exclude distractions.					✓	✓		✓	✓	✓	✓		
b.1 Full size panels with functional controls, switches, instruments and primary and secondary flight controls, which shall be operating in the correct direction and with the correct range of movement.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	For FTD Level 1 as appropriate for the replicated system The use of electronically displayed images with physical overlay incorporating operable switches, knobs and buttons may be acceptable. This option is not acceptable for analogue instruments in FFS.
Functional controls, switches, instruments and primary and secondary flight controls sufficient for the training events to be accomplished, shall be located in a spatially correct area of the flight deck.								✓	✓	✓	✓		The use of electronically displayed images with physical overlay incorporating operable switches, knobs and buttons is acceptable.

JAR-FSTD H

Appendix 1 to JAR-FSTD H.030 (continued)

SECTION

FSTD STANDARDS	FFS LEVEL				FTD LEVEL				FNPT LEVEL				COMPLIANCE	
	A	B	C	D	1	2	3	I	II	III	MCC			
1.1 General														
c.1 Lighting for panels and instruments shall be as per the helicopter.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
Lighting for panels and instruments shall be sufficient for the training events														
c.2 Flight deck ambient lighting environment shall be dynamically consistent with the visual display and sufficient for the training event.	✓	✓												
The ambient lighting should provide an even level of illumination which is not distracting to the pilot.	✓	✓												
d.1 Relevant flight deck circuit breakers shall be located as per the helicopter and shall function accurately when involved in operating procedures or malfunctions requiring or involving flight crew response.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			
e.1 Effect of aerodynamic changes for various combinations of airspeed and power normally encountered in flight, including the effect of change in helicopter attitude, aerodynamic and propulsive forces and moments, altitude, temperature, mass, centre of gravity location and configuration.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Effects of C_g , mass and configuration changes are not required for FNPT Level I.	
Aerodynamic and environment modelling shall be sufficient to permit accurate systems operation and indication.														

SECTION 1

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS	FFS LEVEL				FTD LEVEL				FNPT LEVEL				COMPLIANCE		
	A	B	C	D	1	2	3	I	II	III	MCC				
1.1 General															
e.2 Aerodynamic modelling which includes ground effect, effects of airframe and rotor icing (if applicable), aerodynamic interference effects between the rotor wake and fuselage, influence of the rotor on control and stabilization systems, and representations of nonlinearities due to sideslip, vortex ring and retreating blade stall.															
f.1 Validation flight test data shall be used as the basis for flight and performance and systems characteristics. Representative/generic aerodynamic data tailored to the helicopter with fidelity sufficient to meet the objective tests and sufficient to permit accurate system operation and indication.	✓	✓	✓		✓				✓	✓	✓		Aerodynamic data need not be necessarily based on flight test data.		
g.1 All relevant flight deck instrument indications automatically respond to control movement by a crewmember, helicopter performance, or external simulated environmental effects upon the helicopter	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓				

JAR-FSTD H

Appendix 1 to JAR-FSTD H.030 (continued)

SECTION 1

FSTD STANDARDS	FFS LEVEL				FTD LEVEL				FNPT LEVEL				COMPLIANCE
	A	B	C	D	1	2	3	I	II	III	MCC		
1.1 General													
h.1 All relevant communications, navigation, caution and warning equipment shall correspond to that installed in the helicopter. All simulated navigation aids within range shall be usable without restriction. Navigational data shall be capable of being updated.	✓	✓	✓	✓	✓	✓	✓						For FTD 1 applies where the appropriate systems are replicated.
h.2 Navigation equipment corresponding to that of a helicopter, with operation within the tolerances typically applied to the airborne equipment. This shall include communication equipment (interphone and air/ground communications systems).								✓	✓	✓	✓		
h.3 Navigational data with the corresponding approach facilities. Navigation aids should be usable within range without restriction	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		For FFSS and FTDS the navigation database should be updated within 28 days.
i.1 In addition to the flight crewmember stations, at least two suitable seats for the instructor and an additional observer shall be provided permitting adequate vision to the crewmembers' panel and forward windows. Observer seats need not represent those found in the helicopter but shall be adequately secured to the floor of the flight simulator, fitted with positive restraint devices and be	✓	✓	✓	✓									The Authority will consider options to this standard based on unique cockpit configurations. Any additional seats installed shall be equipped with similar safety provisions.

SECTION 1

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS	FFS LEVEL			FTD LEVEL			FNPT LEVEL			COMPLIANCE		
	A	B	C	D	1	2	3	I	II	III	MCC	
1.1 General												
i.2	of sufficient integrity to safely restrain the occupant during any known or predicted motion system excursion.											The instructor's and observer's seats need not represent those found in the helicopter.

JAR- FSTD H

SECTION 1

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS	FFS LEVEL						FTD LEVEL						FNPT LEVEL						COMPLIANCE						
	A	B	C	D	1	2	3	I	II	III	MCC														
1.1 General																									
j.1 FFS systems shall simulate the applicable helicopter system operation, both on the ground and in flight.	✓	✓	✓	✓																					
Systems shall be operative to the extent that normal, abnormal, and emergency operating procedures appropriate to the simulator application can be accomplished. Once activated, proper system operation shall result from system management by the flight crew and not require input from instructor controls.																									
j.2 FTD Systems represented shall be fully operative to the extent that normal, abnormal and emergency operating procedures can be accomplished. Once activated, proper system operation shall result from system management by the flight crew and not require input from instructor controls.		✓	✓	✓																					
j.3 The systems should be operative to the extent that it should be possible to perform normal, abnormal, and emergency operations appropriate to a helicopter as required for training. Once activated, proper systems operations should result from the system management by the crewmember and not require any further input from the instructor's controls.																									
k.1 The instructor shall be able to control system variables and insert abnormal or emergency conditions into the helicopter systems.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓														
Independent freeze and reset facilities shall be provided.																									

SECTION 1

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS	FFS LEVEL				FTD LEVEL				FNPT LEVEL				COMPLIANCE
	A	B	C	D	1	2	3	I	II	III	MCC		
1.1 General	✓	✓	✓	✓									
1.1 Control forces and control travel which correspond to that of the replicated helicopter. Control forces shall react in the same manner as in the helicopter under the same flight conditions.													For Level A only static control force characteristics need to be tested.
Control forces and control travel shall be representative of the replicated helicopter under the same flight conditions as in the helicopter.				✓	✓	✓	✓						For FTD Level 1 as appropriate for the system training required
Control forces and control travel shall broadly correspond to that of a helicopter.							✓						Only static control force characteristics need to be tested.
Control forces and control travels shall respond in the same manner under the same flight conditions as in a helicopter.								✓	✓	✓			Only static control force characteristics need to be tested.
1.2 Cockpit control dynamics, which replicate the helicopter simulated. Free response of the controls shall match that of the helicopter within the given tolerance. Initial and upgrade evaluation will include control free response (cyclic, collective, and pedal) measurements recorded at the controls. The measured responses shall correspond to those of the helicopter in ground operations, hover, climb, cruise, and auto-rotation.	✓	✓	✓	✓	✓	✓	✓						For helicopters with irreversible control systems, measurements may be obtained on the ground. Engineering validation or helicopter manufacturer rationale will be submitted as justification for ground test or to omit a configuration.
													For FFS requiring static and dynamic tests at the controls, special test fixtures will not be required during the initial evaluations if the FSTD operator's QTG shows both test fixture results and alternate test method results, such as computer data plots, which were obtained concurrently. Use of the alternate method during initial evaluation may then satisfy this test requirement.
													FTD Level 2 data can be representative/generic and need not necessarily be based on flight test data.

JAR- FSTD H**SECTION 1**

Appendix 1 to JAR-FSTD H.030 (continued)

m.1	Ground handling and aerodynamic programming to include the following: Ground effect - hover and transition IGE. (Ground reaction - reaction of the helicopter upon contact with the landing surface during landing to include strut deflections, tire or skid friction, side forces, and other appropriate data, such as weight and speed, necessary to identify the flight condition and configuration.		Level A can utilise generic simulation of ground effect and ground handling.	
	✓	✓	✓	✓
	✓	✓	✓	✓
	✓	✓	✓	✓
	✓	✓	✓	✓
	✓	✓	✓	✓
	✓	✓	✓	✓
	✓	✓	✓	✓
	✓	✓	✓	✓
	✓	✓	✓	✓

SECTION 1

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS		FFS LEVEL					FTD LEVEL					FNPT LEVEL					COMPLIANCE	
		A	B	C	D	1	2	3	I	II	III	MCC						
n.1	1.1 General	Instructor controls for																
		(i) Wind speed and direction	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
		(ii) Turbulence	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
		(iii) Other atmospheric models to support the required training.				✓											Examples: Generic atmospheric models of local wind patterns around mountains and structures..	
		(iv) Adjustment of cloud base and visibility.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
		(v) Temperature and barometric pressure.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
o.1		Representative stopping and directional control forces for at least the following landing surface conditions based on helicopter related data, for a running landing.				✓	✓											
		(i) Dry																
		(ii) Wet (soft surface and hard surface)																
		(iii) Icy																
		(iv) Patchy Wet																
		(v) Patchy Icy																
p.1		Representative brake and tire failure dynamics.				✓	✓											
q.1		Cockpit control dynamics, which replicate the helicopter simulated. Free response of the controls shall match that of the helicopter within the given tolerance. Initial and upgrade evaluation will include control free response (cyclic, collective, and pedal) measurements recorded at the controls. The measured responses shall correspond to those of the helicopter in ground operations, hover, climb,				✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	For helicopters with irreversible control systems, measurements may be obtained on the ground. Engineering validation or helicopter manufacturer rationale will be submitted as justification for ground test or to omit a configuration. For FFS requiring static and dynamic tests at the controls, special test fixtures will not be required during the initial evaluations if the FSTD operator's QTG shows both test fixture results and alternate	

JAR- FSTD H**SECTION 1**

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS	FFS LEVEL					FTD LEVEL			FNPT LEVEL			COMPLIANCE
	A	B	C	D	1	2	3	I	II	III	MCC	
1.1 General												
cruise, and auto-rotation.												
r.1	(1) Transport delay. Transport delay is the time between control input and the individual hardware (systems) responses. As an alternative, a Latency test may be used to demonstrate that the flight simulator system does not exceed the permissible delay.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	For FTD Level 1, only instrument response is required within a maximum permissible delay of 200 milliseconds For Level 'A' & 'B' FFS and Level 2 FTD the maximum permissible delay is 150 milliseconds For Level 'C' & 'D' FFS and Level 3 FTD the maximum permissible delay is 100 milliseconds
	(2) Latency. Relative response of the visual system, cockpit instruments and initial motion system response shall be coupled closely to provide integrated sensory cues. These systems shall respond to abrupt pitch, roll, and yaw inputs at the pilot's position within the permissible delay, but not before the time, when the helicopter would respond under the same conditions. Visual scene changes from steady state disturbance shall occur within the system dynamic response limit but not before the resultant motion onset.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	For FTD Level 1 and FNPT Level I, only instrument response is required within a maximum permissible delay of 200 milliseconds For Level 'A' & 'B' FFS, Level 2 FTD and FNPT Level II and III the maximum permissible delay is 150 milliseconds For Level 'C' & 'D' FFS and Level 3 FTD the maximum permissible delay is 100 milliseconds

SECTION 1

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS	FFS LEVEL			FTD LEVEL			FNPT LEVEL			COMPLIANCE		
	A	B	C	D	1	2	3	I	II	III	MCC	
1.1 General												
s.1 A means for quickly and effectively testing FSTD programming and hardware. This may include an automated system, which could be used for conducting at least a portion of the tests in the QTG.	✓	✓			✓			✓	✓	✓		Recommended for FTD Level 1, FNPT Level I and II. Automatic flagging of "out-of-tolerance" tests results is encouraged.
Self-testing for FSTD hardware and programming to determine compliance with the FSTD performance tests. Evidence of testing shall include FSTD number, date, time, conditions, tolerances, and the appropriate dependent variables portrayed in comparison with the helicopter standard.		✓			✓							
t.1 A system allowing for timely continuous updating of FSTD hardware and programming consistent with helicopter modifications.	✓	✓	✓	✓	✓	✓	✓					
u.1 The FSTD operator shall submit a Qualification Test Guide in a form and manner acceptable to the Authority. A recording system shall be provided that will enable the FSTD performance to be compared with QTG criteria.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
v.1 FSTD computer capacity, accuracy, resolution and dynamic response sufficient for the Qualification Level sought.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
w.1 Daily preflight documentation either in the daily log or in a location easily accessible for review.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		

SECTION 1

JAR-FSTD H

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS				FFS LEVEL			FTD LEVEL			FNPT LEVEL			COMPLIANCE		
				A	B	C	D	1	2	3	I	II	III	MCC	
1.2 Motion System															
a.1	Motion cues as perceived by the pilot shall be representative of the helicopter, e.g., touchdown cues should be a function of the simulated rate of descent.			✓	✓	✓	✓								Motion tests to demonstrate that each axes onset cues are properly phased with pilot input and helicopter response.
b.1	A motion system:														The instructor's and observer's seats need not represent those found in the helicopter.
	Having a minimum of 3 degrees of freedom (pitch, roll, heave) to accomplish the required task.														
	6 degrees of freedom synergistic platform motion system														For level B, a reduced motion performance envelope is acceptable.
c.1	A means of recording the motion response time as required			✓	✓	✓	✓								See para 1.1 (r.1) above.

SECTION 1

Appendix 1 to JAR-FSTD H.030 (continued)

JAR-FSTD H

FSTD STANDARDS	FFS LEVEL				FTD LEVEL			FNPT LEVEL			COMPLIANCE		
	A	B	C	D	1	2	3	I	II	III	MCC		
1.2 Motion System	✓	✓	✓	✓									
d.1 Special effects programming to include the following:													
(1) Runway rumble, oleo deflections, effects of groundspeed and uneven surface characteristics.													
(2) Buffet due to translational lift.													
(3) Buffet during extension and retraction of landing gear.													
(4) Buffet due to high speed and retreating blade stall.													
(5) Buffet due to vortex ring.													
(6) Representative cues resulting from;													
(i) touchdown													
(ii) translational lift.													
(7) Antitorque device ineffectiveness.													
(8) Buffet due to turbulence.													

SECTION 1

JAR- FSTD H

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS	FFS LEVEL				FTD LEVEL				FNPT LEVEL				COMPLIANCE			
	A	B	C	D	1	2	3	I	II	III	MCC					
1.2 Motion System																
e.1 Characteristic vibrations/buffets that result from operation of the helicopter and which can be sensed in the cockpit. Simulated cockpit vibrations to include seat(s), flight controls and instrument panel(s), although these need not be tested independently.																

SECTION 1

JAR-FSTD H

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS	FFS LEVEL				FTD LEVEL				FNPT LEVEL				COMPLIANCE
	A	B	C	D	1	2	3	I	II	III	MCC		
1.3 Visual System													
a.1 Visual system capable of meeting all the standards of this paragraph and the respective paragraphs of validation tests as well as functions and subjective tests as applicable to the Level of Qualification requested by the FSTD operator.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	The choice of the display system and of the field of view requirements should fully consider the intended use of the FSTD. The balance between training and testing/checking may influence the choice and geometry of the display system. In addition the diverse operational requirements should be addressed.	
b.1 Visual system capable of providing at least a 45 degree horizontal and 30 degree vertical field of view simultaneously for each pilot. Visual system capable of providing at least a 75 degrees horizontal and 40 degrees vertical field of view simultaneously for each pilot. "Continuous", cross-cockpit, minimum visual field of view providing each pilot with 150 degrees horizontal and 40 degrees vertical	✓				✓			✓				A minimum of 75 degrees horizontal field of view on either side of the zero degree azimuth line relative to the helicopter fuselage is required.	
b.2 "Continuous," cross-cockpit, minimum visual field of view providing each pilot with 150 degrees horizontal and 60 degrees vertical					✓			✓				A minimum of 75 degrees horizontal field of view on either side of the zero degree azimuth line relative to the helicopter fuselage is required. This will allow an offset per side of the horizontal field of view if required for the training. Where training tasks require extended fields of view beyond the 150 degrees x 60 degrees, then such extended fields of view should be provided.	
b.3 "Continuous" cross cockpit, minimum visual field of view providing each pilot with 180 degrees horizontal and 60 degrees vertical					✓			✓				A minimum of 75 degrees of horizontal field of view on either side of zero degrees azimuth line relative to the helicopter fuselage is required. This will allow an offset per side of the horizontal field of view if required for the training. Where training tasks require extended fields of view beyond the 180 degrees x 60 degrees, then such extended fields of view shall be provided.	

JAR- FSTD H**SECTION 1**

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS	FFS LEVEL				FTD LEVEL				FNPT LEVEL				COMPLIANCE
	A	B	C	D	1	2	3	I	II	III	MCC		
1.3 Visual System													
c.1 A means of recording the visual response time for the visual system shall be provided.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
d.1 Visual cues to assess rate of change of height, translational displacements and rates, during takeoff and landing.	✓	✓											For Level 'A', Visual cueing sufficient to support changes in approach path by using FATO perspective
					✓	✓	✓	✓	✓	✓	✓	✓	
e.1 Test procedures to quickly confirm visual system colour, RVR, focus, intensity, level horizon, and attitude as compared with the specified parameters.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	Statement of compliance required. Test required
f.1 A minimum of 10 levels of occulting. This capability should be demonstrated by a visual model through each channel.					✓	✓	✓	✓	✓	✓	✓	✓	Statement of compliance required. Test required
g.1 Surface (Vernier) resolution shall be demonstrated by a test pattern of objects shown to occupy a visual angle of not greater than 3 arc minutes in the visual display used on a scene from the pilot's eye point.		✓	✓										Statement of compliance required. Test required
h.1 Lightpoint size shall not be greater than 6 arc minutes		✓	✓										This is equivalent to a light point resolution of 3 arc minutes.
													This is equivalent to a light point resolution of 4 arc minutes.

SECTION 1

Appendix 1 to JAR-FSTD H.030 (continued)

JAR-FSTD H

FSTD STANDARDS	FFS LEVEL				FTD LEVEL				FNPT LEVEL				COMPLIANCE			
	A	B	C	D	1	2	3	I	II	III	MCC	FNPTS.	Where applicable	Where applicable	Where applicable	Where applicable
1.3 Visual System																
i.1 Daylight, dusk, and night visual scenes with sufficient scene content to recognise aerodromes, heliports, terrain, and major landmarks around the Final Approach and Take-off (FATO) area and to successfully accomplish low airspeed/low altitude manoeuvres to include lift-off, hover, translational lift, landing and touchdown.																
j.1 A visual database sufficient to support the requirements, including																
	(i)	Specific areas within the database needing higher resolution to support landings, take-offs and ground cushion exercises and training away from a heliport. Including elevated helipad, helidecks and confined areas														
	(ii)	For cross-country flights sufficient scene details to allow for ground to map navigation over a sector length equal to 30 minutes at an average cruise speed.														
	(iii)	For offshore airborne radar approaches (ARA), harmonized visual/radar representations of installations.														
	(iv)	(For training in the use of Night Vision Goggles (NVG) a visual display with the ability to represent various scenes with the required levels of ambient light/colour.														

JAR-FSTD H**SECTION 1**

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS	FFS LEVEL				FTD LEVEL				FNPT LEVEL				COMPLIANCE
	A	B	C	D	1	2	3	I	II	III	MCC		
1.3 Visual System													
k.1 Daylight, twilight (dusk/dawn) and night visual capability for system brightness and contrast ratio criteria as applicable for level of qualification sought.													
Night and Dusk scene	✓	✓											
k.2 The visual system should be capable of producing: Full colour presentations.													
Full colour texture shall be used to enhance visual cue perception for illuminated landing surfaces.													
k.3 The visual system should be capable of producing, as a minimum:													
(1) A scene content comparable in detail with that produced by 6,000 polygons for daylight and 1000 visible light points for night and dusk scenes for the entire visual system.													
(2) A scene content comparable in detail with that produced by 4,000 polygons for daylight and 5000 visible light points for night and dusk scenes for the entire visual system													
(3) A scene content comparable in detail with that produced by 6,000 polygons for daylight and 7000 visible light points for night and dusk scenes for the entire visual system.													
i.1 Surface contrast ratio:													
Demonstration model													
Not less than 5:1.	✓	✓											
Not less than 8:1			✓										

SECTION 1

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS		FFS LEVEL				FTD LEVEL				FNPT LEVEL				COMPLIANCE	
		A	B	C	D	1	2	3	I	II	III	MCC			
1.2	Lightpoint contrast ratio. Not less than 25:1.			✓		✓	✓	✓							
m.1	Highlight Brightness. The minimum light measured at the pilot's eye position should be :														
	14 cd/m ² (4 ft-Lamberts)					✓									
	17 cd/m ² (5ft-Lamberts)						✓	✓							
	20 cd/m ² (6 ft-Lamberts)				✓				✓	✓	✓	✓			

SECTION 1**JAR- FSTD H**

Appendix 1 to JAR-FSTD H.030 (continued)

FSTD STANDARDS	FFS LEVEL				FTD LEVEL				FNPT LEVEL				COMPLIANCE			
	A	B	C	D	1	2	3	I	II	III	MCC	✓	✓	✓	✓	✓
1.4 Sound Systems																
a.1 Significant flight deck sounds, and those, which result from pilot actions corresponding to those of the helicopter shall be provided.	✓	✓	✓	✓	✓	✓	✓									
a.2 Sounds due to engines, transmission and rotors should be available							✓									
b.1 Sound of precipitation, windshield wipers, the sound resulting from a blade strike and a crash condition when operating the helicopter in excess of limitations.					✓	✓	✓									
c.1 Realistic amplitude and frequency of cockpit acoustic environment.							✓									
d.1 The volume control shall have an indication of sound level setting which meets all qualification requirements.					✓	✓	✓									

SECTION 1

JAR-FSTD H

Appendix 1 to JAR-FSTD H.030 (continued)

These standards always refer to the type of helicopter being simulated, except for FNPT, which may be generic. For FNPT, the term “the/a helicopter” is used to represent the aircraft being modelled which can be a specific helicopter type, a family of similar helicopter types or a totally generic helicopter.

Wherever the term runway is used, it includes runways and FATO/TLOF.

INTENTIONALLY LEFT BLANK

INTENTIONALLY LEFT BLANK